



Product Code	Previous Code	Product Description	Watts	Lumens	Volts	Base	Colour (K)	Lifetime (h)	Energy Class	PU	Picture
Biax S 2-pins, Internal Starter, G23 Base										*also available in 2700K and 3500K	
37661	-	F5BX/SPX41/840/MIH	5	265	35	G23	4000*	10 000	B	10	
38984	-	F7 BX/865 2P G23 GE MIH	7	425	47	G23	6500*	10 000	A	10	
38930	-	F7BX/830 2P G23 GE MIH	7	425	47	G23	3000*	10 000	A	10	
37660	-	F7BX/SPX41/840/MIH	7	425	47	G23	4000*	10 000	A	10	
38985	-	F9 BX/865 2P G23 GE MIH	9	600	60	G23	6500*	10 000	A	10	
38929	-	F9 BX/830 2P G23 GE MIH	9	600	60	G23	3000*	10 000	A	10	
37653	-	F9BX/SPX41/840 MIH	9	600	60	G23	4000*	10 000	A	10	
38986	-	F11 BX/865 2P G23 GE MIH	11	900	91	G23	6500*	10 000	A	10	
38928	-	F11 BX/830 2P G23 GE MIH	11	900	91	G23	3000*	10 000	A	10	
37664	-	F11BX/840/2P/S MIH	11	900	91	G23	4000*	10 000	A	10	
Biax S/E 4-pins, Required External Starter, 2G7 Base										*also available in 2700K	
37715	-	F5BX/840/4P 2G7 MIH	5	265	35	2G7	4000*	10 000	B	10	
37716	-	F7BX/840/4P 2G7 MIH	7	425	47	2G7	4000*	10 000	A	10	
37711	-	F9BX/840/4P 2G7 MIH	9	600	60	2G7	4000*	10 000	A+	10	
97926	-	F9BX/830/4P 2G7 MIH GE	9	600	60	2G7	3000*	10 000	A+	10	
37713	-	F11BX/840/4P 2G7 MIH	11	900	91	2G7	4000*	10 000	A+	10	
12603	-	F11BX/865/4P 2G7 MIH	11	900	91	2G7	6500*	10 000	A	10	
97925	-	F11BX/830/4P 2G7 MIH GE	11	900	91	2G7	3000*	10 000	A+	10	
Biax D 2-pins, Internal Starter										*also available in 2700K and 3500K	
70258	78212	F10DBX/T4/LL/830/2P BX 1/10	10	600	64	G24d-1	3000*	12 000	B	10	
70265	78214	F10DBX/T4/LL/840/2P BX 1/10	10	600	64	G24d-1	4000*	12 000	B	10	
70268	78215	F10DBX/T4/LL/865/2P BX 1/10	10	600	64	G24d-1	6500*	12 000	B	10	
70572	78222	F13DBX/T4/LL/830/2P BX 1/10	13	900	91	G24d-1	3000*	12 000	A	10	
70573	78224	F13DBX/T4/LL/840/2P BX 1/10	13	900	91	G24d-1	4000*	12 000	A	10	
70574	78225	F13DBX/T4/LL/865/2P BX 1/10	13	900	91	G24d-1	6500*	12 000	A	10	
13017	-	F18DBXT4/SPX65/865	18	1 200	100	G24d-2	6500*	12 000	B	10	
12864	-	F18DBXT4/SPX41/840	18	1 200	100	G24d-2	4000*	12 000	B	10	
12861	-	F18DBXT4/SPX30/830	18	1 200	100	G24d-2	3000*	12 000	B	10	
35305	-	F26DBXT4/SPX65/865	26	1 800	105	G24d-3	6500*	12 000	B	10	
35252	-	F26DBXT4/SPX41/840	26	1 800	105	G24d-3	4000*	12 000	B	10	
35237	-	F26DBXT4/SPX30/830	26	1 800	105	G24d-3	3000*	12 000	B	10	
Biax D/E LongLast™ 4-pins, Required External Starter, Q24q-1 Base										*also available in 2700K and in 3500K	
70555	78218	F10DBX/T4/LL/830/4P BX 1/10	10	600	64	G24q-1	3000*	20 000	A	10	
70560	78220	F10DBX/T4/LL/840/4P BX 1/10	10	600	64	G24q-1	4000*	20 000	A	10	
Biax D/E LongLast™ 4-pins, Required External Starter										*also available in 2700K and in 3500K	
70583	78227	F13DBX/T4/LL/830/4P BX 1/10	13	900	91	G24q-1	3000*	20 000	A	10	
70584	78229	F13DBX/T4/LL/840/4P BX 1/10	13	900	91	G24q-1	4000*	20 000	A	10	
70587	78232	F13DBX/T4/LL/865/4P BX 1/10	13	900	91	G24q-1	6500*	20 000	A	10	
12866	-	F18DBX/SPX30/830/4P	18	1 200	100	G24q-2	3000*	20 000	A	10	
12870	-	F18DBX/SPX41/840/4P	18	1 200	100	G24q-2	4000*	20 000	A	10	
35235	-	F26DBX/SPX30/830/4P	26	1 800	105	G24q-3	3000*	20 000	A	10	
35236	-	F26DBX/SPX41/840/4P	26	1 800	105	G24q-3	4000*	20 000	A	10	
42798	-	F26DBX/SPX65/865/4P	26	1 710	105	G24q-3	6500*	20 000	A	10	