

## **Emergency**

## Fontburn Emergency Exit Sign 3W 6000K - White



















• LiFePO4 battery• Polycarbonate body with printed legend• Maintained



## **General Data**

Technology	LED
Mounting options	Ceiling Wall
Install Options	20mm Cut Out
Electrical Connector Type	Push fit terminal
Input Cable	0.75-2.5mm <sup>2</sup>
Input Electrical Connection	Neutral P Live
General Application	Commercial   Industrial   Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5



421301	Technical Specification	
Optical Data		
LED Manufacturer / Type	Everlight	
Fixture Luminous Flux (Lm)	39	
Luminaire Efficacy @6000K (lm/W)	39	
LOR %	100	
Photobiological Risk Group	RG0	
<u>Light Source Data</u>		
Colour Temperature (K)	6000	
Light Colour	Daylight	
CRI Ra	70	
Electrical Data		
Wattage (W)	3	
Total Power Consumption (W)	3	
Mains voltage (V)	220 - 240	
Lamp power factor	0.8	
Electrical protection	Class II	
Driver Output (V)	2.5-4	
Control Gear Type CC or CV	Constant Current	
Driver Brand	Lumineux	
Nominal Frequency (Hz)	50/60	
<u>Lifetime Data</u>		
Lifespan L70 B50 @25°C (Hrs)	50000	



421301	Technical Specification
Emergency Data	
Battery Type	LiFeP04
Battery Capacity (mAh)	1500mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Type	Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3
Emergency Output	39
Physical Data	
Housing colour	White RAL 9016
Body material	Polycarbonate
	20
IP Rating	
Diffuser Material	Polycarbonate
Nominal Product Length (mm)	310
Nominal Product Width (mm)	35
Nominal Product Height (mm)	230
Weight (kg)	0.96
Standards and Approvals	
Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001



421301

**Technical Specification** 



