

## Commercial

### Kennick GU10 Dimmable Bulbs - 8 Pack 3000k



Kennick GU10 Dimmable Bulbs - 8 Pack 3000k



### General Data

<b>Technology</b>	LED
<b>Install Options</b>	GU10
<b>Input Electrical Connection</b>	Live   Neutral
<b>General Application</b>	Residential   Commercial
<b>Operating Temperature Range °C</b>	0 - +30
<b>Warranty (Years)</b>	1

430731-MP

Technical Specification

## Optical Data

<b>LED Manufacturer / Type</b>	E2835
<b>Fixture Luminous Flux (Lm)</b>	460
<b>Luminaire Efficacy @3000K (lm/W)</b>	86
<b>LOR %</b>	100
<b>Colour Selectable</b>	No
<b>Beam Angle°</b>	38
<b>Photobiological Risk Group</b>	RG0

## Light Source Data

<b>Energy Class</b>	F
<b>Lm/W</b>	86
<b>Colour Temperature (K)</b>	3000
<b>Light Colour</b>	Warm Light
<b>CRI Ra</b>	80

430731-MP

Technical Specification

## Electrical Data

<b>Wattage (W)</b>	5
<b>Mains voltage (V)</b>	220 - 240
<b>Lamp power factor</b>	0.90
<b>Electrical protection</b>	Class II
<b>Driver Output (V)</b>	DOB
<b>Driver Output Current (mA)</b>	DOB
<b>Control Gear Type CC or CV</b>	Constant Current
<b>SVM</b>	0.86
<b>PstLM</b>	0.41
<b>LED Flicker Rate</b>	26.4
<b>Dimmable</b>	Yes
<b>Dimmable Type</b>	Trailing Edge
<b>Recommended Dimmers</b>	•Varilight V-Pro-JDLP401S •Varilight V-Pro JQP401W•Zano ZGRIDLED150 •Zigbee• BG DM400AP
<b>Driver Brand</b>	Lumineux
<b>Nominal Frequency (Hz)</b>	50/60

## Lifetime Data

<b>Lifespan L70 B50 @25°C (Hrs)</b>	25000
-------------------------------------	-------

430731-MP

Technical Specification

## Physical Data

<b>Housing colour</b>	White RAL9003
<b>Body material</b>	Polycarbonate
<b>IP Rating</b>	20
<b>Diffuser Material</b>	Polycarbonate
<b>Diffuser finish</b>	Optic Lens
<b>Nominal Product Length (mm)</b>	50
<b>Nominal Product Width (mm)</b>	50
<b>Nominal Product Height (mm)</b>	55
<b>Weight (kg)</b>	0.024

## Standards and Approvals

<b>Manufactured In Accordance To</b>	EN 60598-1
<b>CE Mark</b>	Yes
<b>UKCA Mark</b>	Yes
<b>WEEE Symbol</b>	Yes
<b>Certificate Of Conformity</b>	Available on Request
<b>Accredited Members</b>	LIA, ISO9001

