

Commercial

Avon One Fire Rated Downlight 5W 4000K White RAL 9016 60D



• Complies with parts B, C, E and L of Building Regulations • Fully tested for 30, 60 and 90 minutes • Tested for use in Solid Joist, I-Joist and Steel Open Web Joist ceilings • Suitable for solid or stranded cable \varnothing 0.75 – 2.5mm² • Designed to work with insulation • 3000K and 4000K options



General Data

Technology	LED
Mounting options	Ceiling
Install Options	Recessed
Electrical Connector Type	Push Terminal
Input Cable	2-Core \varnothing 0.75-2.5mm
Input Electrical Connection	Live Neutral
Fire Rating	30min 60min 90min
General Application	Commercial Residential
Minimum Void Requirement (mm)	60
Insulation Coverage	Can be covered
Operating Temperature Range °C	-10 - +40
Warranty (Years)	3

430651

Technical Specification

Optical Data

LED Manufacturer / Type	Hongli
Fixture Luminous Flux (Lm)	560
Luminaire Efficacy @4000K (lm/W)	112
LOR %	100
Colour Selectable	No
Beam Angle°	60
Photobiological Risk Group	RG0

Light Source Data

Energy Class	E
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	80

430651

Technical Specification

Electrical Data

Wattage (W)	5
Total Power Consumption (W)	5.5
Mains voltage (V)	220-240
Lamp power factor	0.85
Electrical protection	Class II
Driver Output (V)	60-75
Driver Output Current (mA)	55
Control Gear Type CC or CV	Constant Current
SVM	0.17
PstLM	0.18
LED Flicker Rate	Flicker-free
Dimmable	Yes
Dimmable Type	Trailing Edge
Recommended Dimmers	• Varilight V-Pro-JDLP401S • Zano ZGRIDLED150 • Hamilton VWP1XI_EDITB100 • Schneider GGBL6012LMS
Driver Brand	Luminaireux
Inrush Current (A)	3
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	1.5
Max. Luminaire per 10A C Breaker	95
Max. Luminaire per 13A C Breaker	120
Max. Luminaire per 16A C Breaker	150
Max. Luminaire per 20A C Breaker	175
Max. Luminaire per 10A B Breaker	45
Max. Luminaire per 13A B Breaker	60

430651

Technical Specification

Max. Luminaire per 16A B Breaker	130
---	-----

Max. Luminaire per 20A B Breaker	145
---	-----

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	25000
-------------------------------------	-------

Physical Data

Housing colour	White RAL 9016
-----------------------	----------------

Body material	Sheet Metal Plastic
----------------------	-----------------------

Driver Housing	PC Plastic
-----------------------	------------

IP Rating	65 (front) 20 (back)
------------------	----------------------

IK Rating	8
------------------	---

Zoning Suitability	Zone 1
---------------------------	--------

Diffuser Material	PC Plastic
--------------------------	------------

Diffuser finish	Optic Lens
------------------------	------------

Nominal Product Length (mm)	84
------------------------------------	----

Nominal Product Width (mm)	60
-----------------------------------	----

Nominal Product Height (mm)	50
------------------------------------	----

Cut-Out (mm)	70
---------------------	----

Weight (kg)	0.16
--------------------	------

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN 60598-2-2
--------------------------------------	---------------------------

CE Mark	Yes
----------------	-----

UKCA Mark	Yes
------------------	-----

WEEE Symbol	Yes
--------------------	-----

Certificate Of Conformity	Available on Request
----------------------------------	----------------------

Accredited Members	LIA, ISO9001
---------------------------	--------------

430651

Technical Specification

Product Relations



430649
Avon One Clip-on Bezel - Chrome



430648
Avon One Clip-on Bezel - Satin Nickel



430757
Avon One Clip-on Bezel - Brushed Chrome

