

## Amenity

### Hurworth Mini Wall Pack 15W 3CCT Black



- Tough body construction with polycarbonate diffuser
- LED lifespan 30,000 hours L70
- Standard, emergency and dusk to dawn options available



## General Data

<b>Technology</b>	LED
<b>Mounting options</b>	Surface Mount
<b>Install Options</b>	20mm knock out
<b>Electrical Connector Type</b>	Push Terminal
<b>Input Cable</b>	No
<b>Input Electrical Connection</b>	Live   Neutral   Earth   P Live
<b>General Application</b>	Commercial   Industrial   Educational
<b>Operating Temperature Range °C</b>	-20 - +40
<b>Warranty (Years)</b>	3

410290

Technical Specification

## Optical Data

<b>LED Manufacturer / Type</b>	Epistar
<b>Fixture Luminous Flux (Lm)</b>	1114   1282   1189
<b>Luminaire Efficacy @3000K (lm/W)</b>	74
<b>Luminaire Efficacy @4000K (lm/W)</b>	89
<b>Luminaire Efficacy @6000K (lm/W)</b>	78
<b>LOR %</b>	100
<b>Colour Selectable</b>	Yes
<b>Beam Angle°</b>	105
<b>Photobiological Risk Group</b>	RG0

## Light Source Data

<b>Energy Class</b>	F
<b>Lm/W</b>	89
<b>Colour Temperature (K)</b>	3000   4000   6000
<b>Light Colour</b>	Warm Light   Cool White   Daylight
<b>CRI Ra</b>	80

## Electrical Data

<b>Wattage (W)</b>	15
<b>Total Power Consumption (W)</b>	15 14.3 15.2
<b>Mains voltage (V)</b>	220 - 240
<b>Lamp power factor</b>	0.9
<b>Electrical protection</b>	Class II
<b>Driver Output (V)</b>	27-65
<b>Driver Output Current (mA)</b>	260
<b>Control Gear Type CC or CV</b>	Constant Current
<b>SVM</b>	0.04
<b>PstLM</b>	0.01
<b>LED Flicker Rate</b>	1.04
<b>Dimmable</b>	No
<b>Driver Brand</b>	Luminaireux
<b>Inrush Current (A)</b>	<20
<b>Glow Wire Test (°C)</b>	850
<b>Nominal Frequency (Hz)</b>	50/60
<b>Max. Luminaire per 10A C Breaker</b>	56
<b>Max. Luminaire per 13A C Breaker</b>	72
<b>Max. Luminaire per 16A C Breaker</b>	89
<b>Max. Luminaire per 20A C Breaker</b>	111
<b>Max. Luminaire per 10A B Breaker</b>	33
<b>Max. Luminaire per 13A B Breaker</b>	43
<b>Max. Luminaire per 16A B Breaker</b>	53
<b>Max. Luminaire per 20A B Breaker</b>	67

410290

Technical Specification

## Lifetime Data

<b>Lifespan L70 B50 @25°C (Hrs)</b>	50000
-------------------------------------	-------

## Physical Data

<b>Housing colour</b>	Black RAL 9005
-----------------------	----------------

<b>Body material</b>	ABS
----------------------	-----

<b>Driver Housing</b>	Polycarbonate
-----------------------	---------------

<b>IP Rating</b>	65
------------------	----

<b>IK Rating</b>	8
------------------	---

<b>Diffuser Material</b>	Polycarbonate
--------------------------	---------------

<b>Diffuser finish</b>	Frosted
------------------------	---------

<b>Nominal Product Length (mm)</b>	275
------------------------------------	-----

<b>Nominal Product Width (mm)</b>	185
-----------------------------------	-----

<b>Nominal Product Height (mm)</b>	74
------------------------------------	----

<b>Weight (kg)</b>	0.54
--------------------	------

## Standards and Approvals

<b>Manufactured In Accordance To</b>	EN 60598-1
--------------------------------------	------------

<b>CE Mark</b>	Yes
----------------	-----

<b>UKCA Mark</b>	Yes
------------------	-----

<b>WEEE Symbol</b>	Yes
--------------------	-----

<b>Certificate Of Conformity</b>	Available on Request
----------------------------------	----------------------

<b>Accredited Members</b>	LIA, ISO9001
---------------------------	--------------

410290

Technical Specification

