

Emergency

Draycote Emergency Twin Spot 6W 6000K Self Test - White

IP20

5 YR
Warranty

2 YR
Battery
Warranty

LiFePO4

6000K



UK
CA

CE

• LiFePO4 battery• Polycarbonate body and diffuser• Non maintained• 20mm conduit entry• Loop in / Loop out terminals



General Data

Technology	LED
Mounting options	Wall
Install Options	20mm Cut Out
Electrical Connector Type	Push fit terminal
Input Cable	0.75-2.5mm²
Input Electrical Connection	Neutral Earth P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

410256

Technical Specification

Optical Data

LED Manufacturer / Type	Everlight
Fixture Luminous Flux (Lm)	506
Luminaire Efficacy @6000K (lm/W)	506
LOR %	100
Beam Angle°	100
Photobiological Risk Group	RG0

Light Source Data

Colour Temperature (K)	6000
Light Colour	Daylight
CRI Ra	70

Electrical Data

Wattage (W)	6
Total Power Consumption (W)	6
Mains voltage (V)	220 - 240
Lamp power factor	0.8
Electrical protection	Class I
Driver Output (V)	12-50
Driver Output Current (mA)	300
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50/60

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	30000
------------------------------	-------

410256

Technical Specification

Emergency Data

Battery Type	LiFeP04
Battery Capacity (mAh)	6000mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Type	Non-Maintained
Test Procedure	Self Test
Emergency Duration (Hours)	3
Emergency Output	506

Physical Data

Housing colour	White
Body material	Polycarbonate
IP Rating	65
Diffuser Material	Polycarbonate
Nominal Product Length (mm)	280
Nominal Product Width (mm)	90
Nominal Product Height (mm)	301
Weight (kg)	0.66

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

410256

Technical Specification

