

Emergency

Darwell LED Emergency Bulkhead 3W 6000K White Ni-Cd



- LiFePO4 battery
- Polycarbonate body and diffuser
- Maintained / Non maintained
- 20mm conduit entry
- Loop in / Loop out terminals



General Data

Technology	LED
Mounting options	Ceiling Wall
Install Options	20mm Conduit Entry
Electrical Connector Type	Push fit terminal
Input Cable	0.75-2.5mm ²
Input Electrical Connection	Live Neutral P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

430390

Technical Specification

Optical Data

LED Manufacturer / Type	MLS CO
Fixture Luminous Flux (Lm)	140
Luminaire Efficacy @6000K (lm/W)	140
LOR %	100
Beam Angle°	110
Photobiological Risk Group	RG0

Light Source Data

Colour Temperature (K)	6000
Light Colour	Daylight
CRI Ra	70

Electrical Data

Wattage (W)	3
Total Power Consumption (W)	3
Mains voltage (V)	220 - 240
Lamp power factor	0.8
Electrical protection	Class II
Driver Output (V)	2.8 - 5
Driver Output Current (mA)	350
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50/60

430390

Technical Specification

Physical Data

Housing colour	White RAL 9003
Body material	Polycarbonate
IP Rating	65
Diffuser Material	Polycarbonate
Nominal Product Length (mm)	350
Nominal Product Width (mm)	110
Nominal Product Height (mm)	60
Weight (kg)	0.9

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

