

## Exterior

### Lifford Floodlight AC 30W 4000K - Black



- Diecast aluminium body
- Angled bracket for ease of installation
- Supplied with 1M prewired H05RN-F cable
- Breather valve to prevent condensation



## General Data

<b>Technology</b>	LED
<b>Mounting options</b>	Wall
<b>Install Options</b>	Bracket
<b>Electrical Connector Type</b>	Flying Lead
<b>Input Cable</b>	1M H05RN-F 3-Core
<b>Input Electrical Connection</b>	Live   Neutral   Earth
<b>General Application</b>	Residential   Commercial   Industrial
<b>Operating Temperature Range °C</b>	-20 - +30
<b>Warranty (Years)</b>	3

430019

Technical Specification

## Optical Data

<b>LED Manufacturer / Type</b>	E Bright
<b>Fixture Luminous Flux (Lm)</b>	3396
<b>Luminaire Efficacy @4000K (lm/W)</b>	109
<b>LOR %</b>	100
<b>Colour Selectable</b>	No
<b>Beam Angle°</b>	110
<b>Photobiological Risk Group</b>	RG0

## Light Source Data

<b>Energy Class</b>	F
<b>Lm/W</b>	109
<b>Colour Temperature (K)</b>	4000
<b>Light Colour</b>	Cool White
<b>CRI Ra</b>	80

## Electrical Data

<b>Wattage (W)</b>	30
<b>Total Power Consumption (W)</b>	31.1
<b>Mains voltage (V)</b>	220 - 240
<b>Lamp power factor</b>	0.9
<b>Electrical protection</b>	Class I
<b>Driver Output (V)</b>	DOB
<b>Control Gear Type CC or CV</b>	Constant Current
<b>Dimmable</b>	No
<b>Driver Brand</b>	Lumineux
<b>Nominal Frequency (Hz)</b>	50/60
<b>Surge Protection (kV)</b>	1

430019

Technical Specification

## Lifetime Data

<b>Lifespan L70 B50 @25°C (Hrs)</b>	30000
-------------------------------------	-------

## Physical Data

<b>Housing colour</b>	Black RAL 9017
<b>Body material</b>	Diecast Aluminium
<b>IP Rating</b>	65
<b>IK Rating</b>	8
<b>Diffuser Material</b>	Tempered Glass
<b>Diffuser finish</b>	Clear
<b>Nominal Product Length (mm)</b>	165
<b>Nominal Product Width (mm)</b>	180
<b>Nominal Product Height (mm)</b>	32
<b>Weight (kg)</b>	0.56

## Standards and Approvals

<b>Manufactured In Accordance To</b>	EN 60598-1
<b>CE Mark</b>	Yes
<b>UKCA Mark</b>	Yes
<b>WEEE Symbol</b>	Yes
<b>Certificate Of Conformity</b>	Available on Request
<b>Accredited Members</b>	LIA, ISO9001

