

Emergency

Draycote Emergency Twin Spot 6W 6000K - White



- LiFePO4 battery
- Polycarbonate body and diffuser
- Non maintained
- 20mm conduit entry
- Loop in / Loop out terminals



General Data

Technology	LED
Mounting options	Wall
Electrical Connector Type	Push fit terminal
Install Options	20mm Cut Out
Input Cable	0.75-2.5mm ²
Input Electrical Connection	Neutral Earth P Live
General Application	Commercial Industrial Educational
Operating Temperature Range °C	0 - +30
Warranty (Years)	5

421063

Technical Specification

Optical Data

LED Manufacturer / Type	Everlight
Fixture Luminous Flux (Lm)	354
Luminaire Efficacy @6000K (lm/W)	354
LOR %	100
Beam Angle°	100
Photobiological Risk Group	RG0

Light Source Data

Colour Temperature (K)	6000
Light Colour	Daylight
CRI Ra	70

Electrical Data

Wattage (W)	6
Total Power Consumption (W)	6
Mains voltage (V)	220 - 240
Lamp power factor	0.8
Electrical protection	Class II
Driver Output (V)	12-50
Driver Output Current (mA)	300
Control Gear Type CC or CV	Constant Current
Driver Brand	Lumineux
Nominal Frequency (Hz)	50/60

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	30000
-------------------------------------	-------

421063

Technical Specification

Emergency Data

Battery Type	LiFeP04
Battery Capacity (mAh)	1500mAh
Battery Warranty (Years)	2
Recharge Time (Hours)	24 Hours
Emergency Type	Non-Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3
Emergency Output	354

Physical Data

Housing colour	White
Body material	Polycarbonate
IP Rating	20
Diffuser Material	Polycarbonate
Nominal Product Length (mm)	273
Nominal Product Width (mm)	60
Nominal Product Height (mm)	260
Weight (kg)	0.92

Standards and Approvals

Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

421063

Technical Specification

