

Amenity

Ridgegate Bulkhead 14W 3CCT Emergency Microwave - White



- NEW Twist & Lock geartray for easier installation
- Tough and durable body and polycarbonate diffuser
- Wall and ceiling mount
- LED lifespan 30,000 hours L70
- Standard, microwave, emergency and 3 step dimming options available
- IK08 impact rated



General Data

Technology	LED
Mounting options	Ceiling Wall
Install Options	BESA 20mm knock out
Electrical Connector Type	Push Terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth P Live
General Application	Residential Commercial
Operating Temperature Range °C	0 + 30
Warranty (Years)	3

430155-M3-MW

Technical Specification

Optical Data

LED Manufacturer / Type	HYASiC 3030
Fixture Luminous Flux (Lm)	1158 1276 1196
Luminaire Efficacy @3000K (lm/W)	83.9
Luminaire Efficacy @4000K (lm/W)	98.9
Luminaire Efficacy @6000K (lm/W)	87.9
LOR %	100
Colour Selectable	Yes
Beam Angle°	110
Optics	Symetric
Photobiological Risk Group	RG0

Light Source Data

Energy Class	C
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	>80

Electrical Data

Wattage (W)	14
Total Power Consumption (W)	13.8 12.9 13.6
Mains voltage (V)	220 - 240
Lamp power factor	>0.70
Electrical protection	Class I
Driver Output (V)	70-95
Driver Output Current (mA)	148
Control Gear Type CC or CV	Constant Current
SVM	0.01
PstLM	0.01
LED Flicker Rate	0.39
Dimmable	No
Driver Brand	Lumineux
Inrush Current (A)	<20
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33
Max. Luminaire per 13A B Breaker	43
Max. Luminaire per 16A B Breaker	53
Max. Luminaire per 20A B Breaker	67

430155-M3-MW

Technical Specification

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	>50000
-------------------------------------	--------

Emergency Data

Battery Type	LiFeP04
Battery Capacity (mAh)	1500mAh
Battery Warranty (Years)	1
Recharge Time (Hours)	24 Hours
Emergency Type	Maintained
Test Procedure	Manual
Emergency Duration (Hours)	3
Emergency Output	160

Sensor Data

Sensor Technology	Microwave
Sensor Type	ON/OFF
Max. Mounting Height (M)	6
Hold Time	5s 30s 90s 3min 20min 30min
Detection area (m)	Max. (D x H) 12m x 6m
Daylight Threshold	2Lux 10Lux 25Lux 50Lux Disable
Detection radius (°)	150 (Wall mounted) / 360 (Ceiling mounted)

430155-M3-MW



Technical Specification

Physical Data


Housing colour	White RAL 9016
Body material	ABS
Driver Housing	Polycarbonate
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser finish	Frosted
Nominal Product Length (mm)	316
Nominal Product Width (mm)	316
Nominal Product Height (mm)	83
Cut-Out (mm)	0.828
Weight (kg)	0.806

Standards and Approvals


Manufactured In Accordance To	EN 60598-1 EN60598-2-22
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001



DETECTION PATTERN



Wall mounting pattern (Unit: m)
Suggested installation height: 1.5m



Ceiling mounting pattern (Unit: m)
Suggested installation height: 3m