

Linear

Stanford Anti-Corrosive 19W 4000K 4ft Single - Grey



• High efficacy up to 145LPCW • Anti-distortion housing • Improved thermals utilising aluminium back PCBs • Opal, ribbed polycarbonate diffuser to reduce glare • Stainless steel clips • H3 – High Output Emergency 440lm option available



General Data

Technology	LED
Mounting options	Ceiling Wall Suspended
Install Options	Fixing Bracket
Electrical Connector Type	Screw terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Industrial Commercial Educational
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

430026

Technical Specification

Optical Data

LED Manufacturer / Type	Smalite
Fixture Luminous Flux (Lm)	2500
Luminaire Efficacy @4000K (lm/W)	131
LOR %	100
Colour Selectable	No
Beam Angle°	115
Photobiological Risk Group	RG0

Light Source Data

Energy Class	D
Lm/W	131
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	80

430026

Technical Specification

Electrical Data

Wattage (W)	19
Total Power Consumption (W)	20.2
Mains voltage (V)	220 - 240
Lamp power factor	0.95
Electrical protection	Class I
Driver Output (V)	20-54
Driver Output Current (mA)	350
Control Gear Type CC or CV	Constant Current
Dimmable	Yes
Dimmable Type	Step Dim
Driver Brand	Tridonic
Glow Wire Test (°C)	8
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	2
Max. Luminaire per 10A C Breaker	75
Max. Luminaire per 13A C Breaker	95
Max. Luminaire per 16A C Breaker	120
Max. Luminaire per 20A C Breaker	150
Max. Luminaire per 10A B Breaker	65
Max. Luminaire per 13A B Breaker	90
Max. Luminaire per 16A B Breaker	110
Max. Luminaire per 20A B Breaker	130

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

430026

Technical Specification

Physical Data

Housing colour	421C Grey
Body material	ABS
Driver Housing	Metal casing
IP Rating	65
IK Rating	8
Diffuser Material	Polycarbonate
Diffuser finish	Milky
Nominal Product Length (mm)	1274
Nominal Product Width (mm)	90
Nominal Product Height (mm)	90
Weight (kg)	1.62

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Available on Request
Accredited Members	LIA, ISO9001

