

Linear

Sutton Batten 30W 4000K 6ft Single - White



• Frosted, ribbed polycarbonate diffuser to reduce glare • Improved thermals utilising aluminium back PCBs • Push fit terminals • 20mm conduit entry • Additional screw to secure end cap • H3 – High Output Emergency 440lm option available



General Data

Technology	LED
Mounting options	Ceiling Wall Suspended
Electrical Connector Type	Push fit terminal
Install Options	BESA
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Commercial Educational
Operating Temperature Range °C	0 - +40
Warranty (Years)	5

430042

Technical Specification

Optical Data

LED Manufacturer / Type	MTC
Fixture Luminous Flux (Lm)	3040
Luminaire Efficacy @4000K (lm/W)	160
LOR %	100
Colour Selectable	No
Beam Angle°	120
Photobiological Risk Group	RG0

Light Source Data

Energy Class	C
Lm/W	160
Colour Temperature (K)	4000
Light Colour	Cool White
CRI Ra	80

430042

Technical Specification

Electrical Data

Wattage (W)	30
Total Power Consumption (W)	32
Mains voltage (V)	220 - 240
Lamp power factor	0.95
Electrical protection	Class I
Driver Output (V)	36-53
Driver Output Current (mA)	350
Control Gear Type CC or CV	Constant Current
SVM	0.01
PstLM	0.02
LED Flicker Rate	0.26
Dimmable	No
Driver Brand	Lifud
Inrush Current (A)	≤16A
Nominal Frequency (Hz)	50/60
Surge Protection (kV)	2
Max. Luminaire per 10A C Breaker	35
Max. Luminaire per 13A C Breaker	50
Max. Luminaire per 16A C Breaker	65
Max. Luminaire per 20A C Breaker	75
Max. Luminaire per 10A B Breaker	28
Max. Luminaire per 13A B Breaker	40
Max. Luminaire per 16A B Breaker	52
Max. Luminaire per 20A B Breaker	60

430042

Technical Specification

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Physical Data

Housing colour	White RAL 9003
-----------------------	----------------

Body material	Sheet Metal
----------------------	-------------

Driver Housing	Polycarbonate
-----------------------	---------------

IP Rating	20
------------------	----

IK Rating	4
------------------	---

Diffuser Material	Polycarbonate
--------------------------	---------------

Diffuser finish	Frosted
------------------------	---------

Nominal Product Length (mm)	1829
------------------------------------	------

Nominal Product Width (mm)	64
-----------------------------------	----

Nominal Product Height (mm)	62
------------------------------------	----

Weight (kg)	1.85
--------------------	------

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
--------------------------------------	------------

CE Mark	Yes
----------------	-----

UKCA Mark	Yes
------------------	-----

WEEE Symbol	Yes
--------------------	-----

Certificate Of Conformity	Available on Request
----------------------------------	----------------------

Accredited Members	LIA, ISO9001
---------------------------	--------------

430042

Technical Specification

