

A-Type Distribution Boards Incoming Devices

Switch Disconnecter

- Meets the requirements of EN 60947-3
- Maximum cable termination capacity is 50mm²
- Utilization category of AC22

Current Rating (A)	Poles	Product Code
100	2	AV2100
125	2	AV2125

Double Pole RCCB

- Meets the requirements of EN 61008
- Equipped with transient suppression filter
- Voltage 230/400V and 50/60Hz
- Double module: Type AC
- Maximum cable termination capacity is 25mm² for ratings up to 63A and 35mm² for 80A/100A ratings

Current Rating (A)	Sensitivity (mA)	Poles	Product Code
63	30	2	EE63/30/2
63	100	2	EE63/100/2
63	300	2	EE63/300/2
80	30	2	EE80/30/2
100	30	2	EE100/30/2
100	100	2	EE100/100/2
100 time delay	100	2	EES100/100/2

A-Type Distribution Boards Accessories

Description	Product Code
Vertical Stacking Kits	
Stacking kit for 270mm width	DAXSK08
Stacking Kit for 323mm width	DAXSK11
Stacking Kit for 377mm width	DAXSK14
Stacking Kit for 430mm width	DAXSK17
Stacking Kit for 484mm width	DAXSK20
Stacking Kit for 555mm width	DAXSK24
Earth Bar Kits	
Earth Bar	DAXEB
Earth Bar isolation kit	DBXL
Door Lock Kits	
Cylinder door lock	DBXCL
Padlock bracket kit	DBXPL
Busbar Terminal Blanks	
Pack of 10 x busbar terminal blanks	DAXTP
MCB Blanks	
4 x Triple Pole MCB blanks and 12 x busbar terminal blanks	DBXBP
5 x Single Pole MCB blanks and 5 x busbar terminal blanks	DBXBM
5 x Half Pole MCB blanks	DBXBH

A-Type Distribution Boards Direct Connection Kits

Cable termination (mm ²)	Product Code
35	DBXD0
70	DBXD1

Loadlimiter 63

