

# SLIM DUCT 225 x 25 mm AND 300 x 25 mm SYSTEMS

Manufactured from flame retardant material conforms to DIN 4102/B1 and UL94 V2. Colour white, and suitable for use with centrifugal fans with 100mm spigot.

	DIMENSIONS 225 mm		DIMENSIONS 300 mm	
	DESCRIPTION	CODE	DESCRIPTION	CODE
	Slim duct channel (225 x 1 m length) Slim duct channel (225 x 2.0 m length)	8147* 8168*	Slim duct channel (300 x 1 m length) Slim duct channel (300 x 2.0 m length)	8156* 8157*
	Connector	8149*	Connector	8158*
	Horizontal 90° bend	8150*	Horizontal 90° bend	8159*
	Horizontal 45° bend	8151*	Horizontal 45° bend	8160*
	Vertical 90° bend	8152*	Vertical 90° bend	8161*
	Vertical 45° bend	8196*	Vertical 45° bend	8197*
	Plenum (Ø 100)	8153*	Plenum (Ø 100)	8162*
	Round to Rectangular Adapter Ø 100	8146*	Round to Rectangular Adapter Ø 100	N/A
	Liner/Plenum Connector Ø 100	8174*	Liner/Plenum Connector Ø 100	8174*
	Single Airbrick Adaptor	8425*	Single Airbrick Adaptor	8435*
	Double Airbrick Adaptor	8426*	Double Airbrick Adaptor	N/A
	Airbrick Insert - White Airbrick Insert - Brown Airbrick Insert - Beige Airbrick Insert - Terracotta	8440* 8441* 8442* 8443*	Airbrick Insert - White Airbrick Insert - Brown Airbrick Insert - Beige Airbrick Insert - Terracotta	8440* 8441* 8442* 8443*
	Duct support clip	8155*	Duct support clip	8155*
	Fire Wrap Fire Wrap Sleeve	8820* 8933*	Fire Wrap Fire Wrap Sleeve	8825* 8934*
	Adaptor (225 x 25 to 300 x 25)	8140*	Adaptor (225 x 25 to 300 x 25)	8140*

\* Available only in UK