

Starline[®],

PVC, nicht flammverbreitend

Starline[®],

PVC, non-flame propagating



Material	Code	Mechan.	UV stabil.	Temp.
PVC-U	EN 211	> 1000 N	<input checked="" type="checkbox"/>	-25°C/+60°C

Außeneck
external angle

Inneneck
internal angle

Flachwinkel
flat angle

Stoßabdeckung
cover joint




Sockelleistenkanal
skirting trunking

aufwärts
upward



abwärts
downward

50x170mm	SLS 50/170	art	SAE 50/170	SIE 50/170	SFWU 50/170	SFWD 50/170	SK 50/170
	3m	ps	1	1	1	1	10
	180m	pl	20	20	10	10	200
	036 054	ref	036 058	036 057	036 730	036 731	036 059



Trapezkanal
chamfered dado trunking

50x170mm	SLC 50/170	art	CAE 50/170	CIE 50/170	CFW 50/170	CK 50/170
	3m	ps	1	1	1	10
	180m	pl	20	20	10	200
	036 055	ref	036 067	036 066	036 729	036 068



Wandkanal
square dado trunking

50x170mm	SLQ 50/170	art	QAE 50/170	QIE 50/170	QFW 50/170	QK 50/170
	3m	ps	1	1	1	10
	180m	pl	20	20	9	200
	036 056	ref	036 071	036 070	036 898	036 072