



- 30 meters range to the Receiver
- Comfort/Economy or On/Off modes
- Unique RF address to avoid interference
- Clear LCD display showing room temperature
- Large control dial
- Frost protection
- 5-30°C set point range

Transmitter	
Power Supply	2xAAA 1.5V batteries
Battery Lifespan	1 year
Temperature Adjustment Range	5-30°C
Temperature Display Range, Scale	3-51°C, 1°C
Temperature Frost Protection	5°C (non adjustable)
Switching Differential	+/- 1°C
Dimensions	86 x 86 x 32mm
Transmission Frequency	433Mhz
Transmission Distance	80m open, 30m indoors
Mounting Method	Wall/Surface
Receiver	
Power Supply	230Vac, 50Hz
Contact Rating	16A, 250Vac (Volt Free contact)
Insulation class	2
Flexible Wire Size	1.5mm <sup>2</sup>
Rigid Wire Size	1.5mm <sup>2</sup>
Dimensions	86 x 86 x 55, when mounted
Mounting	Wall using supplied backbox
Transmitter and Receiver	
Operating Temperature	0-50°C
Storage Temperature	10-60°C
Protection Rating	IP21

**CHOICE RSTAT3RF**  
Wireless Digital Thermostat



- Bi-Metallic temperature sensing element
- Suitable for surface or switch box mounting
- -5 to 25°C set point range
- Tamper resistant cover fitted with accelerator heater

Power Supply	230 Vac, 50 Hz
Temperature control range	-5 to 25°C
Load rating (1-3)	10A / 250 Vac
Ambient Max	T50
Protection Rating	IP20
Dimensions	78mm x 78mm x 36mm

**CHOICE FSTAT1**  
Frost Thermostat



- 30 meters range to the Receiver
- Economy and Comfort Operation
- Unique RF address to avoid interference
- 24 hour or 7 day programmable
- 6 programmable events per day
- Button press back-lit operation
- Frost protection
- 5-35°C set point range

Transmitter	
Power Supply	4xAAA 1.5V Alkaline batteries
Battery Lifespan	1 year
Temperature display range	5-35°C (increment 0.1)
Temperature control range	0- 50°C (increment 0.5)
Program time increment	10 minutes
Temperature accuracy	+/- 1°C
Switching Differential	+/- 0.5°C or +/- 0.1°C selectable
Operating Temperature	0 – 50°C
Clock Accuracy	<1sec / day
Protection Rating	IP30
Dimensions	110 x 104 x 21.5mm
Transmission Frequency	868Mhz
Transmission Distance	80m open, 30m indoors
Mounting	Wall or free standing using table stand
Receiver	
Power supply	230Vac, 50Hz
Contact rating	16A, 250Vac (Volt Free contact)
Insulation class	2
Flexible Wire Size	0.5-1.5mm
Rigid Wire Size	0.5-2.5mm
Dimensions	88 x 88 x 39.4mm
Wall mounting	Industry standard
Complies with	EN60730-1, EN60730-2-7, EN60730-11

**CHOICE RSTAT5RF**  
Wireless Digital Programmable Thermostat



- Easy fixing to all hot water cylinders
- Suitable for use on uninsulated and foam lagged cylinders
- Cylinder strap and hooks provided
- Pipe mounting attachment included

Switch Action	SPPT Type 1CL
Switch Rating	16(4) A, 230 Vac
Sensing Element	Bi-metal
Temperature setting Range	0°C to 90°C
Differential	4°C +2°C
Max Surface Temperature	110°C
Protection	IP40
Fixing	Plastic coated spring wire (1800mm) with hooks

**CHOICE CSTAT**  
Cylinder Thermostat

