# **≫**Dimplex®

## CFSE Commercial Fan Heater



#### Technical Details

Controls  Digitally controlled, accurate electronic thermostat. Timer modes: 7 Day Programmable User Timer Continuous heat modes: Manual, Runback, Fan Only, Off  Controller functions  Adaptive Start Advance time period Heat selection (High/Low) Bluetooth for control  Controller UI  Off-board control only. Requires pairing with Bluetooth remote.  Element  Metal sheathed (CFS30E) Finned metal sheathed (CFS60E)  Fan  Axial (CFS30E), Centrifugal (CFS60E)  Airflow  400m3/h (CFS30E), 750m3/h (CFS60E)  Noise  37d(B)a (CFS30), 50d(B)a (CFS60E)  Installation  Included wall bracket  Construction / Finish  Flectric reset out-out (CFS30E) (115C)		
tions  Advance time period Heat selection (High/Low) Bluetooth for control  Controller UI  Off-board control only. Requires pairing with Bluetooth remote.  Element  Metal sheathed (CFS30E) Finned metal sheathed (CFS60E)  Fan  Axial (CFS30E), Centrifugal (CFS60E)  Airflow  400m3/h (CFS30E), 750m3/h (CFS60E)  Noise  37d(B)a (CFS30), 50d(B)a (CFS60E)  Installation  Included wall bracket  Construction / Finish  Steel case with plastic mouldings Traffic White (RAL9016) with black grille and bracket	Controls	Timer modes: 7 Day Programmable User Timer Continuous heat modes:
remote.  Element Metal sheathed (CFS30E) Finned metal sheathed (CFS60E)  Fan Axial (CFS30E), Centrifugal (CFS60E)  Airflow 400m3/h (CFS30E), 750m3/h (CFS60E)  Noise 37d(B)a (CFS30), 50d(B)a (CFS60E)  Installation Included wall bracket  Construction / Steel case with plastic mouldings Traffic White (RAL9016) with black grille and bracket		Advance time period Heat selection (High/Low)
Finned metal sheathed (CFS60E)  Fan Axial (CFS30E), Centrifugal (CFS60E)  Airflow 400m3/h (CFS30E), 750m3/h (CFS60E)  Noise 37d(B)a (CFS30), 50d(B)a (CFS60E)  Installation Included wall bracket  Construction / Steel case with plastic mouldings Traffic White (RAL9016) with black grille and bracket	Controller UI	
Airflow 400m3/h (CFS30E), 750m3/h (CFS60E)  Noise 37d(B)a (CFS30), 50d(B)a (CFS60E)  Installation Included wall bracket  Construction / Steel case with plastic mouldings Traffic White (RAL9016) with black grille and bracket	Element	
Noise 37d(B)a (CFS30), 50d(B)a (CFS60E)  Installation Included wall bracket  Construction / Steel case with plastic mouldings Traffic White (RAL9016) with black grille and bracket	Fan	Axial (CFS30E), Centrifugal (CFS60E)
Installation Included wall bracket  Construction / Steel case with plastic mouldings Traffic White (RAL9016) with black grille and bracket	Airflow	400m3/h (CFS30E), 750m3/h (CFS60E)
Construction / Steel case with plastic mouldings Finish Traffic White (RAL9016) with black grille and bracket	Noise	37d(B)a (CFS30), 50d(B)a (CFS60E)
Finish Traffic White (RAL9016) with black grille and bracket	Installation	Included wall bracket
Safaty Electric reset cut-out (CES30E) (115C)		
Manual reset cut-out (CFS60E) (13C)	Safety	Electric reset cut-out (CFS30E) (115C) Manual reset cut-out (CFS60E) (85C)
IP Rating IP24 (CFS30E) IPX4 (CFS60E)	IP Rating	IP24 (CFS30E) IPX4 (CFS60E)

Warranty & Approvals		
Approvals	CE, BEAB	
Warranty	2 Years	
Country of Origin	UK	
Manufacturer	Glen Dimplex Heating & Ventilation (GDC Group Ltd)	


## Product Description


The CFSE is a robust fan heater suited for general purpose commercial and light industrial use. The CFSE are offered in either 3kW or powerful 6kW versions.

## Key Features

- Seven-day timer and temperature control (programmed via bluetooth remote)
- Features energy-saving Adaptive Start technology
- Heavy duty corrosion resistant case
- Adjustable wall bracket
- 2 heat settings and cool blow
- Wall controller included
- Complies with Lot 20 of ERP directive

#### Dimensions





Model/Item No. (EAN-Code	081148	081155			
501139+Item No.)	CFS30E	CFS60E			
Heat Output (kW)	3	6			
Supply voltage	230V 1P&N	230V 1P&N			
Dimension A (mm)	262	360			
Dimension B (mm)	306	386			
Dimension C (mm)	495	565			
Dimension D (mm)	530	630			
Weight (kg)	7.6	13.5			
Packaging Details					
Height (mm)	325	450			
Width (mm)	450	570			
Depth (mm)	450	530			
Weight (kg)	7.8	16.5			
Ti	8	6			
Hi	3	3			
Pallet Quantity (2.4m high)	24	18			