

# Electrak® 26 power track system

dual circuit system (dark green)



Selection chart (p. 16-17)  
Dimensions and technical information (p. 22-25)

Approved to ASTA Standard 138 and ISO 9001 : 2008  
Conforms to BS EN 60439-2 : 2008. Fully complies with the requirements of BS 7671 : 2008 IEE Wiring Regulations  
A compact system that can be installed in floor voids as low as 48 mm

Pack	Cat. Nos.	Track system components
		The dual power track system has both standard and low noise / clean earth systems incorporated
		<b>Electrak 26 dual circuit track lengths</b>
		Track lengths fit together using the integral connectors on each length
		Track lengths should always be secured using the integral floor fixing brackets
		300 mm socket centres
1	KA3123	1.2 m, 4 sockets, 2 floor fixing brackets
1	KA3243	2.4 m, 8 sockets, 2 floor fixing brackets
1	KA3363	3.6 m, 12 sockets, 3 floor fixing brackets
		<b>Track feed unit</b>
1	KF3010	With one 25 mm diameter hole suitable for MICC, armoured cables or single core cables in conduit
		<b>Flexible interlinks</b>
		Can be used to overcome obstructions or as corners where required
1	KW3000	Excluding cables and conduit
1	KW3010	1.2 m flexible metal conduit
1	KW3020	2.4 m flexible metal conduit
		<b>Special fixing brackets</b>
		Required when track is raised off surface level
		Brackets raise track by 21 mm and should be spaced 600 mm apart
1	DZ1210	For fitting under track body and track feed
1	DZ1230	For fitting under integral track connectors

Pack	Cat. Nos.	Tap-off units
		Tap-off length is determined by the cable and not the conduit length, e.g. a 3 m tap-off has 3 m of cable and 2.8 m of flexible metal conduit <sup>(1)</sup>
		Tap-off units in excess of 3 m should only be used if they contain a fuse or if the power track is protected by a 32 A rated protective device
		<b>Standard 32 A unfused</b>
		16 mm Ø, L, N, PE
1	DP1332	3 m
1	DP1532	5 m
		<b>Standard 13 A fused</b>
		16 mm Ø, L, N, PE
1	DP1313	3 m
1	DP1513	5 m
		<b>Standard 13 A 543.7 fused</b>
		16 mm Ø, L, N, PE
1	DP1327	3 m
1	DP1527	5 m
		<b>Low noise / clean earth 32 A unfused</b>
		16 mm Ø, CE, L, N, PE
1	JP2332	3 m
1	JP2532	5 m
		<b>Low noise / clean earth 13 A fused</b>
		16 mm Ø, CE, L, N, PE
1	JP2313	3 m
1	JP2513	5 m
		<b>Low noise / clean earth 13 A 543.7 fused</b>
		20 mm Ø, CE, L, N, PE
1	JP2327	3 m
1	JP2527	5 m
		<b>Dual circuit 32 A unfused</b>
		20 mm Ø, CE, L1, N1, L2, N2, PE
1	KP3328	3 m
1	KP3528	5 m

(1) Tap-offs are supplied as standard with flexible metal conduit  
For alternative wiring solutions, contact us on +44 (0) 845 600 6266