

DOMESTIC CONSUMER UNITS

ISOLATOR CONTROLLED - LEFT HAND INCOMER

Specification - IP20 Certified - 

List No.	Description	Pack Qty
M3CU4	4 module 2 way 100A DP Isolator	1
M3CU6	6 module 4 way 100A DP Isolator	1
M3CU8	8 module 6 way 100A DP Isolator	1
M3CU10	10 module 8 way 100A DP Isolator	1
M3CU14	14 module 12 way 100A DP Isolator	1
M3CU16	16 module 14 way 100A DP Isolator	1
M3CU18	18 module 16 way 100A DP Isolator	1
M3CU21	21 module 19 way 100A DP Isolator	1



M3CU14

ISOLATOR CONTROLLED - RIGHT HAND INCOMER

Specification - IP20 Certified - 



M3CU14R

List No.	Description	Pack Qty
M3CU4R	4 module 2 way 100A DP Isolator	1
M3CU6R	6 module 4 way 100A DP Isolator	1
M3CU8R	8 module 6 way 100A DP Isolator	1
M3CU10R	10 module 8 way 100A DP Isolator	1
M3CU14R	14 module 12 way 100A DP Isolator	1
M3CU16R	16 module 14 way 100A DP Isolator	1
M3CU18R	18 module 16 way 100A DP Isolator	1
M3CU21R	21 module 19 way 100A DP Isolator	1

ISOLATOR CONTROLLED - SPD INCLUDED (WHILST STOCKS LAST!)

Standard of Compliance - EN 61643-11
Specification - IP20

Certified - 

List No.	Description	Pack Qty
M3CU8SP	8 module 4 way 100A DP Isolator	1
M3CU10SP	10 module 6 way 100A DP Isolator	1
M3CU14SP	14 module 10 way 100A DP Isolator	1
M3CU16SP	16 module 12 way 100A DP Isolator	1
M3CU18SP	18 module 14 way 100A DP Isolator	1
M3CU21SP	21 module 17 way 100A DP Isolator	1



M3CU8SP

Note - Surge protection device included min 15kA I_{max}

TYPE 2 SURGE PROTECTION KIT



Specification -

- Type 2, 40kA I_{max}
- Earthing system - TN-S / TN-C-S
- Live located at bottom for ease of install
- Supplied with E&N cables
- If the incoming supply is protected by, equal to or less than a 125A fuse no MCB is required

Standard of Compliance - BS EN61643-11

Certified - TÜV



List No.	Description	Earth Type	Modules	Qty
NSA2-240	1P + N 230V AC	TN-S/TN-C-S	1	1

A TYPE RCBO - SWITCHED LINE + NEUTRAL DP - SPACE SAVER 230V A TYPE

SL + N A TYPE RCBO

Compact switched neutral RCBO's provide double pole switching for complete isolation of faulty circuits. Reduces installation and commissioning time. Suitable for TN & TT systems.



87mm

Standard of Compliance - BS EN 61009-1
Breaking Capacity - 6kA

Certified - 

List No.	Rating & Curve	Modules	Pack Qty
RCBO1-6/30SSAX	6A 30mA 'B'	1	1
RCBO1-10/30SSAX	10A 30mA 'B'	1	1
RCBO1-16/30SSAX	16A 30mA 'B'	1	1
RCBO1-20/30SSAX	20A 30mA 'B'	1	1
RCBO1-32/30SSAX	32A 30mA 'B'	1	1
RCBO1-40/30SSAX	40A 30mA 'B'	1	1

ARC FAULT DETECTION DEVICE / RCBO AFDD - 1P+N 230V A TYPE

ARC FAULT DETECTION DEVICE

Single module AFDD with combined A Type RCBO protects against arc faults, earth fault currents (inc. pulsating DC currents), overload and short circuits.



Standard of Compliance - BS EN 61009-1, BS EN 62606
Breaking Capacity - 6kA

Certified - 

List No.	Rating & Curve	Modules	Pack Qty
AFDD6B1-6A	6A 30mA 'B'	1	1
AFDD6B1-10A	10A 30mA 'B'	1	1
AFDD6B1-16A	16A 30mA 'B'	1	1
AFDD6B1-20A	20A 30mA 'B'	1	1
AFDD6B1-32A	32A 30mA 'B'	1	1
AFDD6B1-40A	40A 30mA 'B'	1	1