




## Horizontal Switched Interlocked Socket - With Backbox IP44



- Prima series designed as compact horizontal interlocked socket-outlet for distribution boards and standard applications.
- Padlockable handle in open or closed position, with max 3 mm Ø padlock.
- Compliance with standards IEC/EN 60309-1/2/4 and 60947-3.
- Rated current from 16A up to 32A.
- Operating voltage option from 110V up to 400V.
- Thermoplastic body.
- Supplied with backbox

## PM16/454146LW

### Switched socket with mechanical interlock

TECHNICAL DATA		REGISTRY	
Rated current	16A	Net weight	0.77KG
Frequency	50/60Hz	Gross Weight	0.83KG
Poles	3P+N+ 	EAN Code	8014950051519
Clock Position	6h	Min order quantity	1.00
Storage room temperature MAX	+70 °C	<b>REFERENCE STANDARDS</b>	<b>STANDARDS</b>
Protection degree	IP44	EN 60309-4:2007/A1:2012	2014/35/EU (LVD)
Rated operating voltage	400V•	EN 60309-1:1999	2012/19/EU (WEEE)
Manufacturing material	Thermoplastic	EN 60309-1:1999/A1:2007	2011/65/EU (RoHS)
		EN 60309-1:1999/A1AC:2014	
		EN 60309-2:1999/A2:2012	
		EN 60309-4:2007	
		EN 60309-1:1999/A2:2012	
		EN 60309-2:1999	
		EN 63000:2018	
		EN 60309-2:1999/A1:2007	