






Picture	Code	Version	Colour	Specification	W	M / O
EternaPro - CARINA CIRCULAR RANGE (EMERGENCY VERSIONS - LITHIUM CELL TECHNOLOGY)						
	CSLEDCR	Colour temperature selectable standard	WH	LED 17W 35,000 hrs IP65 3100K (1250 lm) 4200K (1350 lm) 6400K (1300 lm) Ø: 325mm, D: 110mm	5	1 / 8
	CSLEDWH	Colour temperature selectable standard	WH		5	1 / 8
	CSLEDCREM3	Colour temperature selectable emergency	WH		5	1 / 8
	CSLEDWHEM3	Colour temperature selectable emergency	WH		5	1 / 8
	MSCSLEDCR	Colour temp. selectable MW	WH		5	1 / 8
	MSCSLEDWH	Colour temp. selectable MW	WH		5	1 / 8
	MSCSLCREM3	Colour temp. selectable MW + emergency	WH		5	1 / 8
	MSCSLWHEM3	Colour temp. selectable MW + emergency	WH		5	1 / 8
	SDCSLEDCR	Colour temp. selectable Step Dim MW	WH		5	1 / 8
	SDCSLEDWH	Colour temp. selectable Step Dim MW	WH		5	1 / 8
	SDCSLCREM3	Colour temp. selectable Step Dim MW + EM3	WH		5	1 / 8
	SDCSLWHEM3	Colour temp. selectable Step Dim MW + EM3	WH		5	1 / 8
	CFLEDWHSC	Standard	WH	LED 17W 4200K 1350 lm 35,000 hrs IP65 Ø: 325mm, D: 110mm	5	1 / 8
	CFLWHEM3SC	Emergency	WH		5	1 / 8
	MSLEDWHSC	MW sensor	WH		5	1 / 8
	MSLWHEM3SC	MW sensor + emergency	WH		5	1 / 8
	CFLEDMINSC	Standard compact Carina	WH	LED 9W 4200K 875 lm 40,000 hrs IP65 Ø: 273mm, D: 90mm	5	1 / 10
	MSLEDMINSC	MW sensor compact Carina	WH		5	1 / 10
EternaPro - SPARROWHAWK AMENITY RANGE						
	SHFULLBK	Full diffuser standard	BK	LED 12W 4200K 800 lm 25,000 hrs IP65 Ø: 305mm, D: 95mm	5	1 / 10
	SHFULLWH	Full diffuser standard	WH		5	1 / 10
	SHEYEBK	Eyelid diffuser standard	BK		5	1 / 10
	SHEYEWH	Eyelid diffuser standard	WH		5	1 / 10
	SHFULLMWBK	Full diffuser MW sensor	BK		5	1 / 10
	SHFULLMWWH	Full diffuser MW sensor	WH		5	1 / 10
	SHEYEMWBK	Eyelid diffuser MW sensor	BK		5	1 / 10
	SHEYEMWWH	Eyelid diffuser MW sensor	WH		5	1 / 10
	MINIFULLBK	Full diffuser compact fitting	BK	LED 6W 4200K 380 lm 35,000 hrs IP66 Ø: 215mm, D: 80mm	5	1 / 10
	MINIFULLWH	Full diffuser compact fitting	WH		5	1 / 10
	MINIEYEBK	Eyelid diffuser compact fitting	BK	LED 6W 4200K 330 lm 35,000 hrs IP66 Ø: 200mm, D: 80mm	5	1 / 10
	MINIEYEWH	Eyelid diffuser compact fitting	WH		5	1 / 10

**Carina
Circular
Range**