

INSULATION continued

Heatshrink Sleeves continued

DUAL WALLED ADHESIVE LINED 1.2m length.

| Part Number | Inside Diameter (mm) (before shrinking) | Inside Diameter (mm) (after shrinking) |
|-------------|--|---|
| DW48 | 4.8 | 1.6 |
| DW64 | 6.4 | 2.2 |
| DW95 | 9.5 | 3.2 |
| DW12 | 12.7 | 4.2 |
| DW19 | 19.1 | 6.3 |
| DW25 | 25.4 | 8.5 |
| DW38 | 38.0 | 13.5 |



MANUFACTURED
IN THE UK

Insulation Sleeving

PVC SLEEVING

Supplied in a wide range of colours and sizes. Alternative diameters and wall thicknesses also available. Ideal for cable or harnessing covering. Coil size 100 metres. Nominal wall thickness 0.5mm.



| Part Number | Reel Part Number | Inside Dia (mm) |
|-------------|------------------|-----------------|
| PVC1.5* | N/A | 1.5 |
| PVC2* | PVC2*-REEL | 2.0 |
| PVC3* | PVC3*-REEL | 3.0 |
| PVC4* | PVC4*-REEL | 4.0 |
| PVC5* | N/A | 5.0 |
| PVC6* | N/A | 6.0 |
| PVC8* | N/A | 8.0 |
| PVC10* | N/A | 10.0 |
| PVC12* | N/A | 12.0 |

* Suffix Part Number with the colour required e.g. green/yellow = PVC3G/Y.

Available in Red (RED), Yellow (YEL), Blue (BLU), Green/Yellow (G/Y), Black (BLK), Grey (GRY), White (WHI) and Brown (BRO).

PVC OVER SLEEVING MULTI REELS

High quality live, neutral and earth PVC over sleeving supplied on easy to use drums.

| Part Number | Description |
|-------------|--------------------------|
| PVC2DMR | 60m G/Y 20m BLU & BRO |
| PVC3DMR | 60m G/Y 20m BLU & BRO |
| PVC4DMR | 40m G/Y 10m BLU & BRO |

HEAT RESISTANT SLEEVING

Available in Black, White, Blue, Brown and Red. Coil size 25 metres.

| Part Number | Bore Size (mm) |
|-------------|----------------|
| HRS4 | 4 |
| HRS6 | 6 |
| HRS8 | 8 |
| HRS10 | 10 |
| HRS12 | 12 |
| HRS16 | 16 |

