

# Rhine

LED flood light

- Diecast aluminium body
- Surge protection
- Slim profile
- 1m of H05RN-F 3 x 1mm<sup>2</sup> cable

**3** 3 Years Standard Warranty

**1000V** (10W,20W) Surge Protection (L to GND)

**2000V** (30W,50W) Surge Protection (L to GND)



Optional Connector  
KCWP3IN

## General Specification

Voltage	220-240Vac 50-60Hz
CRI	>80
Life Time	30,000h
Power Factor	>0.90
Ambient Temp	-20°C to 40°C
Housing	Diecast aluminum



## Order Code


KFLDHS10Q465-W30-BLK  
KFLDHS10Q465-W40-BLK  
KFLDHS10Q465-W65-BLK

KFLDHS20Q465-W30-BLK  
KFLDHS20Q465-W40-BLK  
KFLDHS20Q465-W65-BLK


KFLDHS30Q465-W30-BLK  
KFLDHS30Q465-W40-BLK  
KFLDHS30Q465-W65-BLK

KFLDHS50Q465-W30-BLK  
KFLDHS50Q465-W40-BLK  
KFLDHS50Q465-W65-BLK


## Dimensions



KFLDHS10Q465



KFLDHS20Q465  
KFLDHS30Q465



KFLDHS50Q465



1m lead



Angled bracket for easy installation

Order Code	Power	Beam Angle	Finish	CCT	Lumen
KFLDHS10Q465	10W	110°	Black	3000K	<b>650lm</b>
				4000K	<b>750lm</b>
				6500K	<b>750lm</b>
KFLDHS20Q465	20W	110°	Black	3000K	<b>1400lm</b>
				4000K	<b>1500lm</b>
				6500K	<b>1500lm</b>
KFLDHS30Q465	30W	110°	Black	3000K	<b>2150lm</b>
				4000K	<b>2250lm</b>
				6500K	<b>2250lm</b>
KFLDHS50Q465	50W	110°	Black	3000K	<b>3900lm</b>
				4000K	<b>4000lm</b>
				6500K	<b>4000lm</b>

## Accessory

Type	Order Code	Description
Connector	KCWP3IN	IP67 In-line Connector