Horizontal Switched Interlocked Socket - With Backbox IP44

- Prima series designed as compact horizontal interlocked socket-outlet for distribution boards and standard applications.
- Padlockable handle in open or closed position, with max 3 mm Ø padlock.
- Compliance with standards IEC/EN 60309-1/2/4 and 60947-3.
- Rated current from 16A up to 32A.
- Operating voltage option from 110V up to 400V.
- Thermoplastic body.
- Supplied with backbox

PM16/454124LW

Switched socket with mechanical interlock

TECHNICAL DATA	
Rated current	16A
Frequency	50/60Hz
Poles	2P+
Clock Position	4h
Storage room temperature MAX	+70°C
Protection degree	IP44
Rated operating voltage	110V
Manufacturing material	Thermoplastic

REGISTRY	
Net weight	0.75KG
Gross Weight	0.75KG
EAN Code	8014950051496
Min order quantity	1.00

REFERENCE STANDARDS	STANDARDS
EN 60309-4:2007/A1:2012	2012/19/EU (WEEE)
EN 63000:2018	2011/65/EU (RoHS)
EN 60309-1:1999/A1:2007	2014/35/EU (LVD)
EN 60309-2:1999/A2:2012	
EN 60309-4:2007	
EN 60309-1:1999	
EN 60309-2:1999/A1:2007	
EN 60309-1:1999/A2:2012	
EN 60309-1:1999/A1AC:2014	
EN 60309-2:1999	