



AERMLED2/60/WW



Features

High performance maintenance free LED Panel

Tpa as standard

30W Panel outperforms 3x14W T5

Low glare and even light distribution for multiple applications

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Panel Pod Self-Test emergency option

Panel Pod sensor option

Surface mounting frame option

Powered by Philips

LED lifespan L80 B10 54,000 hours

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface/Recessed/Suspended
Diffuser Rating	Tp(a)
LED Life	
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Depth (mm)	10
Accessories	AERMLED/SK, AERMLED/60/SMF, AERMLED/60/CGCB/KIT

Technical Information

Wattage	29W
Lumens Delivered	2891lm
Lm/W	100lm
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 40°C

Datasheet generated from <https://onetimepim.com> last updated Friday, July 30, 2021 11:32:29 AM

