



### Main

Range of product	Mita
Product name	Cableline 40 Cableline 50 Consort Dado Consort Delta 105 Ultimate 60 Ultimate 62
Product or component type	Mounting plate
Colour tint	White
Quantity per set	Set of 15

### Complementary

Trunking dimension	100 x 40 mm 100 x 60 mm 150 x 60 mm 190 x 62 mm 180W x 52 mm 180V x 52 mm 180 x 52 mm 145W x 40 mm 145V x 40 mm 145 x 40 mm 100 x 50 mm
Number of gangs	1 gang
Device mounting	Flush
Mounting support	Trunking
Material	UPVC (unplasticized polyvinyl chloride)

### Environment

Standards	EN 50085-1: 2005 EN 50085-2-1
Ambient air temperature for operation	-5...60 °C
Environmental characteristic	RoHS compliant

## REACH

---

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1826 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations