

Common characteristics

- Dimensions: 86 x 86 mm (1 gang), 86 x 146 mm (2 gang)
- Fix screws: M3.5 x 30 mm
- Mounting box:
 - SB251 (F) 1 gang GPAT1G25 (S)
 - SB252 (F) 2 gang GPAT2G25 (S)



LSKT1GR



GPRCDFCU



GSW1G2W



GSWA1G2W

30mA RCD protected devices



- BS 7288
- BS 7288/BS 5733

Cat. no.	Gang	Description	Qty
LSKT1GR	1	Active control socket-outlet*	1
LSKT2GR	1	Active control socket-outlet*	1
LSKT2GRP	1	Passive control socket-outlet**	1
GPRCDSKT1G	1	Passive control switched socket-outlet**	1
GPRCDSKT2G	1	Passive control switched socket-outlet**	1
GPRCDFCU	1	Passive control fused connection unit**	1

* Electronic latch/Active control - device will fail safe in the event of loss of supply. Suitable for domestic use.

** Mechanical latch/Passive control - device will only trip in the event of a fault. Suitable for freezers and commercial applications.

10 AX plate switches



- BS EN 60669-1
- BS EN 60947-3 (GSWIS02)

Cat. no.	Gang	Description	Qty
GSW1G1W	1	1 way	10
GSW1G2W	1	2 way	10
GSW2G2W	2	2 way	10
GSW3G2W	3	2 way	10
GSW4G2W	4	2 way	10
GSWISO2		3 pole isolator*	10
GSWTPS		6 A triple pole switch	10
GSWINT		intermediate	10
GSW1G2WR	1	2 way retractive*	10
GSW1G2WRP	1	2 way retractive marked 'press'	10
GSW1G2WRB	1	2 way retractive marked with bell symbol*	10

* 10 A rated

- Dimensions: 1-3 gang 86 x 86 mm, 4 gang 86 x 146 mm
- Mounting box:
 - 1-2 gang 16 mm
 - 3 gang 25 mm
 - 4 gang 25 mm
- Fix screws: M3.5 x 20 mm

10 AX architrave switches



Cat. no.	Gang	Description	Qty
GSWA1G2W	1	10 AX 2 way architrave	10
GSWA2G2W	2	10 AX 2 way architrave	10

- Dimensions: 33 x 86 mm (1 gang), 33 x 148 mm (2 gang)
- Mounting box:
 - SBA251A (F) GPAT1G16A (S) 1 gang
 - SBA252A (F) GPAT2G16A (S) 2 gang
- Fix screws: M3.5 x 20 mm
- BS EN 60669-1