

Common characteristics

- Dimensions: 86 x 86 mm (1 gang), 86 x 146 mm (2 gang)
- Fix screws: M3.5 x 30 mm
- Mounting box:
 - SB471 (F) 1 gang GPAT1G47 (S)
 - SB472 (F) 2 gang GPAT2G47 (S)
 - SB251 (F) GPAT1G25 (S)



G45ACCUN

45 A DP switches and cooker controls



- BS 4177
- BS 5733
- BS EN 60669-1

Cat. no.	Gang	Description	Qty
GCKR45A	1	45 A DP	5
GCKRN45A	1	45 A DP with neon	5
GCKR45A2G	2	45 A DP	5
GCKRN45A2G	2	45 A DP with neon	5
G45ACCU		45 A Cooker control unit with 13 A socket-outlet	1
G45ACCUN		45 A Cooker control unit with 13 A socket-outlet and neon	1
G45CX		45 A connection unit	10

Shaver socket-outlet



GSHVSKT



- BS EN 61558-2-5

Cat. no.	Description	Qty
GSHVSKT	shaver socket-outlet with dual 115 / 230 V output	1
GADAPTSVR	shaver adaptor 1 A fuse (fuse to BS 646)	20

- Dimensions: 146 x 86 mm

Communication outlets



GSKTCOAX2G



- BS EN 41003
- BS 3041 (where applicable)

Cat. no.	Gang	Description	Qty
GTELMAS	1	single telephone master	10
GTELSEK	1	single telephone secondary	10
GSKTCOAX	1	single direct connection TV	10
GSKTCOAX2G	1	twin direct connection TV	10

- Mounting box: SB251 (F) GPAT1G25 (S)

Euro modular plates



GEURO4

Cat. no.	Description
GEURO1	1 module
GEURO2	2 module
GEURO4	4 module