# Product datasheet Characteristics

## EZ9E8MCU

## 8 way Metal Easy9 Consumer Unit

#### Main

Range of product	Easy9
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Provided equipment	Earth/neutral terminal block Busbar
Type of front cover	Plain
Product compatibility	Easy9 MCB Easy9 RCCB Easy9 RCBO Easy9 switch Easy9 SPD

### **Complementary**

Enclosure mounting	Surface
Number of 18 mm modules per row	8
Total number of 18 mm modules	8
Number of horizontal rows	1
Number of ways	8 ways
Enclosure material	Metal
[ln] rated current	100 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	125 mm <sup>2</sup> incoming
Comb busbar and distribution block compatibility	YES
Product weight	4.39 kg
Height	276.8 mm
Width	320.8 mm
Depth	119.55 mm
Colour	White ( RAL 9003 )

#### **Environment**

standards	BS EN 61439-3 BS 7671: amendment 3	
standards	BS EN 61439-3	
IP degree of protection	IPxx D on top IP3x with cover	
IK degree of protection	IK05	
overvoltage category	II	