

Common characteristics

- Dimensions: 86 x 86 mm (1 gang), 86 x 146 mm (2 gang)
- Fix screws: M3.5 x 30 mm
- Mounting box:
 - SB251 (F) 1 gang GPAT1G25 (S)
 - SB252 (F) 2 gang GPAT2G25 (S)



GSKTSW2G2



GSKTSWDPOB2G



GSKTSW3G
(not to scale)



GSKT5A1G

13 A socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GSKT1G	1	unswitched	10
GSKT2G	2	unswitched	5
GSKTSW1G	1	switched	10
GSKTSW2G2	2	switched	5
GSKTSWDP1G	1	DP switched	10
GSKTSWDP2G	2	DP switched	5
GSKTSWDP1G2G	1-2	DP switched converter	5

13 A DP outboard socket-outlet



Cat. no.	Gang	Description	Qty
GSKTSWDPOB2G	2	switched	5

13 A 3 gang socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GSKTSW3G	3	switched and fused	5

- Dimensions: 86 x 205 mm
- Mounting box: GPAT3G25 (S)

Round pin socket-outlet



- BS 546

Cat. no.	Gang	Description	Qty
GSKT2A1G	1	2 A unswitched	10
GSKT5A1G	1	5 A unswitched	10
GSKT15A1G	1	15 A unswitched	10
GSKTSW15A1G	1	15 A switched	10
GSKTSW15A1GN	1	15 A switched with neon	10

Note: All 2 gang socket-outlets include twin earth terminals as standard, enabling high integrity earthing. To aid flush installation 35 mm steel boxes are recommended.