

GGBL5011

Lisse - fuse connection unit - LED - 1 gang - 13 A - white moulded



Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Fuse connection unit
Device presentation	Complete product
Colour tint	White moulded
Quantity per set	Set of 10

Complementary

Pilot light	LED
Actuator	Rocker
Number of gangs	1 gang
Material	Urea (carbamide)
Device mounting	Wall mounted
Fixing mode	By screws
Rated current	13 A, 250 V AC
Connections - terminals	Screw terminals
Type of packing	Carton
Width	87 mm
Height	87 mm
Depth	28 mm
Product weight	0.105 kg

Environment

standards	BS 1363
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.