


Common characteristics

- Dimensions: 88 x 88 mm (1 gang), 88 x 148 mm (2 gang)
- Fix screws: M3.5 x 25 mm and 30 mm



GU3250 WSS



GU3220WPC



GU3234WSS

13 A unswitched socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GU3250***	1	unswitched	1
GU3260***	2	unswitched	1

13 A switched socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GU3210***	1	switched	1
GU3220***	2	switched	1
GU3211***	1	switched with neon	1
GU3221***	2	switched with neons	1
GU3210D***	1	DP switched	1
GU3220D***	2	DP switched	1

13 A DP outboard rocker switched socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GU3430***	2	switched	1
GU3431***	2	switched with clean earth and neon's	1
GU3432***	2	switched with red rockers, clean earth and neon's	1
GU3433***	2	switched with clean earth and non standard	1
GU3434***	2	switched with red rockers, clean earth, non standard and neon's	1

Note: All 2 gang socket-outlets include twin earth terminals as standard, enabling high integrity earthing. To aid flush installation 35 mm steel boxes are recommended.

Note: Replace *** with suffix code to denote finish / interior colour required:

Note: Replace ** with suffix code to denote finish required:

WSS: Stainless steel / white; **WPN:** Pearl nickel / white; **BPC:** Polished chrome / black; **BBZ:** Bronze / black

BSS: Stainless steel / black; **BPB:** Polished brass / black; **WPC:** Polished chrome / white

WPW: Painted white / white; **WPB:** Polished brass / white; **BBN:** Black nickel / black