

Common characteristics

- Dimensions: 88 x 88 mm (1 gang), 88 x 148 mm (2 gang)
- Fix screws: M3.5 x 25 mm and 30 mm



GU3280WPB



GU3251WSS



GU1212BSS

Round pin socket-outlet



- BS 546

Cat. no.	Gang	Description	Qty
GU3270***	1	2 A unswitched	1
GU3280***	1	5 A unswitched	1
GU3290***	1	15 A switched	1

13 A floor socket-outlet



- BS 1363

Cat. no.	Gang	Description	Qty
GU3251W**	1	unswitched	1
GU3252W**	2	unswitched	1

All 2 gang socket-outlets include twin earth terminals as standard, enabling compliance with regulation 607 (BS 7671) – high integrity earthing. To aid flush installation 35 mm steel boxes are recommended. Floor socket-outlet interiors are manufactured from high impact thermoplastic for strength.

16 AX plate switches



- BS EN 60669-1
- BS EN 60947-3 (GU1213***)

Cat. no.	Gang	Description	Qty
GU1212***	1	2 way SP	1
GU1212R***	1	10 A 2 way retractive*	1
GU1222***	2	2 way SP	1
GU1232***	3	2 way SP	1
GU1242***	4	2 way SP	1
GU1262***	6	2 way SP	1
GU1213***		3 pole isolator**	1
GU1214***	1	intermediate	1

* 16 A

** 10 A

- Dimensions: 88 x 88 mm (1-3 gang), 88 x 148 mm (4-6 gang)

Note: Replace *** with suffix code to denote finish / interior colour required:

Note: Replace ** with suffix code to denote finish required:

WSS: Stainless steel / white; **WPN:** Pearl nickel / white; **BPC:** Polished chrome / black; **BBZ:** Bronze / black

BSS: Stainless steel / black; **BPB:** Polished brass / black; **WPC:** Polished chrome / white

WPW: Painted white / white; **WPB:** Polished brass / white; **BBN:** Black nickel / black