
Product data sheet Characteristics

GGBL3060

Lisse - unswitched socket - 13 A - 2 gangs - 230 V - white



Main

Main		· · · · · · · · · · · · · · · · · · ·
Range	Lisse	
Aesthetic name	White moulded	
Product or component type	Unswitched socket	
Device presentation	Complete product	
Outlet standard	British	
Colour tint	Matt white	
Quantity per set	Set of 5	
Type of packing	Carton	

Complementary

Complementary		
Switch function	1-pole	
Rated current	13 A, 250 V AC 50 Hz	
Actuator	Rocker	
Number of gangs	2 gangs	
Fixing mode	By screws	:
Connections - terminals	Screw terminals	,
Material	Urea (carbamide)	
Type of installation	Indoor	
Depth	22 mm	
Width	148 mm	
Height	87 mm	
Product weight	0.123 kg	

Environment

Standards	BS 1363-2
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1642 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	