

Inspiration starts here  
**PRODUCT SELECTOR**

**EURO DATACOM MODULES**

RJ45 CAT 5e ANGLED 1 MODULE 25 X 50MM	RJ45 CAT 5e 1 MODULE 25 X 50MM	TELEPHONE MASTER 1 MODULE 25 X 50MM	TELEPHONE SECONDARY 1 MODULE 25 X 50MM	BNC 50Ω 1 MODULE 25 X 50MM
---	---	--	---	----------------------------------



**FUNCTIONAL MODULES**

White	K5844WHI	K5845WHI	K5820WHI	K5821WHI	K5801WHI
Black		K5845BLK	K5820BLK	K5821BLK	

Enhanced Cat 5 performance.  
 Suitable for both 568A and 568B wiring schemes.

**MOUNTING BOXES**  
 Minimum box depth 35mm standard  
 ISO/IEC 11801  
 EN 50173  
 TIA 568  
 EN 41003

Enhanced Cat 5 performance.  
 Suitable for both 568A and 568B wiring schemes.

**MOUNTING BOXES**  
 Minimum box depth 35mm standard  
 ISO/IEC 11801  
 EN 50173  
 TIA 568  
 EN 41003

**MOUNTING BOXES**  
 Minimum depth 35mm  
 BS 6312-2EN 41003

**MOUNTING BOXES**  
 Minimum depth 35mm  
 BS 6312-2

50 Ohm crimp connector suitable for use with RG58, URM43, URM76 and Beldon 9907 type co-axial cables.

**MOUNTING BOXES**  
 Minimum box depth 35mm

Mains operated products and extra low voltage modules must not be installed within the same frontplate.  
 Refer to BS 7671:2008 for details.