


## SE48B250

Loadcentre KQ - distribution board - B type - 3 phase  
- 250A - 16 ways



### Main

Range	Acti 9
Product name	Load centre KQ II B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Door Enclosure Front cover Pan assembly Shielded neutral bar suitable for 25 mm <sup>2</sup> Earth terminal block suitable for 25 mm <sup>2</sup>

### Complementary

Enclosure mounting	Surface
[Ie] rated operational current	250 A at 400/415 V AC
Incomer device	Lugs Lugs Switch disconnecter - 4P MCCB - 4P Terminal block - 4P RCCB - 30...300 mA - 4P
Protection device type	Miniature circuit breaker (MCB) (plug-on type ) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type ) as outgoer
Number of ways	16 way(s) of 3P outgoer
Cable entry	Through knock-out at top and bottom Through knock-out at side
Height	808 mm
Width	470 mm
Depth	139 mm

### Environment

IP degree of protection	IP2x B internal confirming to BS EN 60529 IP3x external confirming to BS EN 60529
-------------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.