

LED Backlit Panel

PF>0.9

No Flicker

TP(b) Diffuser

UGR19>

CCT: 4500K & 6000K

Ra>80



Luxlite Ltd

ADD: Units 17 & 18 Matrix Way,
Buckshaw Village,
Chorley,
Lancashire,
PR7 7ND

TEL: 01253 890 211

www.luxliteuk.com



www.luxliteuk.com

Features:

Square appearance, smooth lines, simple and generous style, comfortable and low glare, with no dark areas.

Specification:

Part No.	Dimension (mm)	CCT	Power	LED Q'ty
LUX-BL36W123	295*1195*30			48PCS
LUX-BL36W664	595*595*30	4500K - 6000K	36W	32PCS
LUX-BL60W126	595*1195*30		60W	72PCS

LED Type	SMD2835
Driver	AGT Non Flicker driver
Light Efficiency	106LM/W
Beam Angle	120°
CCT	4500-6000K
Flicker	Flicker free
Input	AC200~240V, 50/60Hz
PF	0.90
Ra	Ra>80
Materials	AL+ PC
IP Grade	IP20
Luminaire Type	Class II
Ambi	-20°C~50°C
Ambient	-40°C~70°C
Lifetime	30,000hrs

Application:

Indoor Lighting, Universities, Hospital, Conference rooms, Show rooms, Factories, Offices, Chain stores, Supermarkets etc.



LUX-BL36W123

Dimension: 295*1195*30mm



LUX-BL36W664

Dimension: 595*595*25mm



LUX-BL60W126

Dimension: 595*1195*25mm



Packing Details:

Part No.	Power	N.W.	Carton Size	Q'ty/CTN	G.W.	40'HQ
LUX-BL36W123	36W	2kg	L1250*W330*H205mm	6PCS	13kg	4000pcs
LUX-BL36W664		2kg	L650*W630*H205mm		13kg	4000pcs
LUX-BL60W126	60W	4kg	L1250*W630*H170mm	4PCS	17kg	2000pcs