Rigid Ducting | Round

Duct Sleeve – 1m



Code	Duct Size	Connection	Material	Colour	Fire Standards	Manufactured to
2100-4	Ø100mm	N/A	Extruded uPVC	White	UL94V0	ISO9001
2100-5	Ø125mm	N/A	Extruded uPVC	White	UL94V0	ISO9001
2100-6	Ø150mm	N/A	Extruded uPVC	White	UL94V0	ISO9001

Duct – 2m Straight Length of Ducting



Code	Duct Size	Connection	Material	Colour	Fire Standards	Manufactured to
1200-4	Ø100mm	Duct	Extruded uPVC	White	UL94V0	ISO9001
1200-5	Ø125mm	Duct	Extruded uPVC	White	UL94V0	ISO9001
1200-6	Ø150mm	Duct	Extruded uPVC	White	UL94V0	ISO9001

Straight Duct Connector



Ø100mm EasyPipe 100

Ø100mm

7,850mm²

Ø125mm EasyPipe 125



Free Area 12,266mm²

Ø150mm EasyPipe 150



Free Area 17,263mm²

Pa							
3.5							
3	Ø100mn	m					
2.5	Ø125mn	n	_/_				
2	Ø150mn	m				/	
1.5					_/		
1		_/					
0.5							
0							
	10	20 30	40	50	60	70	80
			Volume flo	w (l/s)			

Resistance data in Pascals (Pa)									
Size	@5l/s	@10l/s	@15l/s	@20l/s	@25l/s	@30l/s	@35l/s	@40l/s	
Ø100mm	0	0.2	0.4	0.8	1.3	1.8	2.3	3	
Size	@10l/s	@20l/s	@30l/s	@40l/s	@50l/s	@60l/s	@70l/s	@80l/s	
Size Ø125mm	@10l/s	@20l/s 0.1	@30l/s 0.3	@40l/s 0.6	@50l/s	@60l/s 1.5	@70l/s 2.1	@80l/s 2.5	

Code	Duct Size	Description	Connection	Material	Colour	Fire Standards	Manufactured to
493	Ø100mm	Straight duct connector	Male	HIPS (High Impact Polystyrene)	White	UL94HB	ISO9001
593	Ø125mm	Straight duct connector	Male	HIPS (High Impact Polystyrene)	White	UL94HB	ISO9001
693	Ø150mm	Straight duct connector	Male	HIPS (High Impact Polystyrene)	White	UL94HB	ISO9001