

SSN - GRIPBOND/SAVES NAILS**Usage:**

Fast bonding adhesive with gap filling properties

Cure Time:

48 hours depending on thickness and temperature.

Info:

Solvent-free



SSN

OTHER ADDITIONAL INFORMATION**Description:**

An environmentally friendly, advanced technology formula offering instant grab and tough permanent bond on virtually any porous or non-porous surfaces.

SAVES NAILS SF is a low odour, 99% VOC free, water clean-up construction adhesive. Cures to form a high strength bond. Contains no harmful raw materials, making it safe for the environment, safe for the user and safe on substrates.

Uses:

Bond It SAVES NAILS SF is ideal for adhering panelling, plasterboard, cove base, window sills, styrofoam, carpet tack strips, aluminium furring strips, tub surrounds, fireplaces, loose floor/wall tiles, plywood, aluminium, steel, wood, concrete, cork, general repairs to wood, fixing hardboard and plywood and as a general adhesive.

It is ideal for use on:

- plastics
- wood
- concrete
- brick
- plasterboard
- carpet
- metal

Preparation:

Ensure all surfaces to be bonded are clean, dry and free from grease or any contaminants that may hinder adhesion.

Application:

Cut tip off cartridge. Cut nozzle to required width of bead at a 45° angle. Place cartridge in a standard cartridge gun and apply as required. Once applied, surfaces should be firmly pressed together to aid bonding. If heavy panels are being bonded, temporary mechanical support may be necessary for 24 hours. **SAVES NAILS SF** does not need to be flashed.

Limitations:

This adhesive should not be applied to building materials that bleed oils, plasticisers or solvents.

Container Size:

EU3 plastic cartridge.

Shelf Life:

12 months.

Storage Conditions:

Store in cool, dry conditions.

Disposal of Containers:

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety:

Avoid eye contact.

Avoid prolonged contact with skin.

Thoroughly wash hands with soap and water after use.

Keep out of reach of children

See separate material safety data sheet for full handling, use and storage.

Specification Summary

Flammability	Non flammable
Application Temperature	2°C to 60°C
Service Temperature	-40°C to +82°C
Consistency	Thick paste- gun grade
Slump	None
Shrinkage	Approx 16%
Staining	None
Tack Free Time	5 minutes
Water Resistance	Good when fully cured
Bond Strength	145 psi when fully cured

Container Sizes:

Code: BDPGE

Size: EU3

Barcode: 5060021360564

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.