

PMS - PANEL MOUNT

Description:
Yellow, Blue & Red Panel Mounts

Ingress Protection:
IP44



PMS110-16

OTHER ADDITIONAL INFORMATION

**HT413-4
HT423-4**



> current:16A 32A > voltage:110-130V~2P+E > IP44 splashproof 	earth contact position		4h	
	rated current(A)		16 32	
	pole		3	
	dimension(mm)	a	69	71
		b	69	71
c		56	56	
d		56	56	
e		30	29	
f	47	61		
g	50	55		
cable nominal cross-section area(mm ²)		1.5-4	2.5-10	

**HT413
HT423**



> current:16A 32A > voltage:220-250V~2P+E > IP44 splashproof 	earth contact position		6h	
	rated current(A)		16 32	
	pole		3	
	dimension(mm)	a	69	71
		b	69	71
c		56	56	
d		56	56	
e		30	29	
f	47	61		
g	50	55		
cable nominal cross-section area(mm ²)		1.5-4	2.5-10	

**HT414
HT424**



> current:16A 32A > voltage:380-415V~3P+E > IP44 splashproof 	earth contact position		6h	
	rated current(A)		16 32	
	pole		4	
	dimension(mm)	a	69	71
		b	69	71
c		56	56	
d		56	56	
e		25	29	
f	51	61		
g	43	55		
cable nominal cross-section area(mm ²)		1.5-4	2.5-10	