

SGALV - BRIGHT ZINC GALVE SPRAY

Description:

A bright zinc and aluminium powder based spray used for the cosmetic finishing and protection of previously galvanised surfaces where the component has been cut or welded, thereby exposing metal to the air. Zinc is a sacrificial metal and will prevent oxidation and corrosion. Resins in the coating cause it to bond firmly to the substrate.



SGALV

OTHER ADDITIONAL INFORMATION

Benefits:

- Zinc content assists in corrosion prevention
- Resistant to salt spray and weathering
- Excellent heat resistance
- Aluminium powder to make for colour comparison with galvanised surface
- Can be used on previously coated surfaces
- High purity powders
- Excellent adhesion
- Quick drying

Technical Data:

Appearance: Silver grey paint

Odour: Characteristic paint aroma

Contents: Blend of modified alkyd resin, zinc and aluminium powders (31.7%), treated clay, xylene, butyl acetate, acetone and 1-methoxy-2-propanol in a butane/propane propellant

Storage: Below 50°C

Solubility: Insoluble in water

Flash Point: < 0°C

Temperature range: 150 °C continuous 400 °C intermittent

Relative Density: 1.015

Laid down film: Zinc Content 35%. Thickness of film 30-60 microns

Pack Sizes: 12 x 400ml cans

Directions for use: Ensure surfaces to be coated in clean, dry and free from grease. Shake can until agitator ball can be heard and then for a further 1 to 2 minutes. Spray from 25-30 cm, building up layers in light coats. Allow 10 minutes drying time.