

SCCS - CUTTING AND TAPPING FLUIDS

Description

A ready to use cutting and tapping fluid specially formulated to improve tool performance and extend tool life. It contains additives to prevent pitting, galling and metal seizure and is suitable for use on aluminium and steel.



OTHER ADDITIONAL INFORMATION

- Benefits:**
 - For cutting, tapping, reaming and turning.
 - Extreme pressure additives
 - High pressure, frothy discharge to aid penetration.
 - Prolongs tool life and improves machined finish
 - Reduces heat build up
 - Incorporates corrosion inhibitors.

- Technical Data:**

- Appearance:** Brown, frothy liquid-viscosity 300cPs
- Odour:** Sweet solvent odour
- Contents:** Blend of naphthenic lubricants, petroleum wax, bituments, polyisbutylenes, minor quantities, of xylene and white spirit, viscosity improvers, extreme pressure, additives, corrosion inhibitors and hydrocarbon propellants.
Non- chlorinated

- Storage:** Below 50°C
- Flash Point:** <0°C
- Solubility:** Insoluble in water
- Temperature range:** Designed for use at ambient temperatures
- Relative density:** 0.840
- Pack Sizes:** 12 x 400 ml cans
- Directions for Use:** Shake can well before use. Spray tool area to be treated. Repeat if necessary.

- Caution:** Do not spray onto very hot surfaces or near naked flames.