



Surface mounting enclosure, 4 mounting locations

**Part no.** M22-I4  
**216539**  
**EL Number** 4355387  
**(Norway)**

Product name	Eaton Moeller® series M22 Accessory Surface mounting enclosure
Part no.	M22-I4
EAN	4015082165390
Product Length/Depth	80 millimetre
Product height	56 millimetre
Product width	186 millimetre
Product weight	0.279 kilogram
Certifications	CSA-C22.2 No. 14-05 UL UL 508 CSA CSA File No.: 012528 CSA-C22.2 No. 94-91 CE IEC/EN 60947-5 UL File No.: E29184 UL Category Control No.: NKCR CSA Class No.: 3211-03
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Surface mounting enclosure
Public Consumption	Yes
Product Family Description	ES-PMCC-ICP-Eaton RMQ-Titan M22 Modular pilot devices
Globally Marketable	Yes

Enclosure color	Gray
Enclosure material	Plastic
Fitted with:	High-grade steel screws
Knockouts	2 x M20/25 (cable entry knockout at the side, 1 x each side) 2 x M20 (cable entry knockouts at the top) 2 x M20 (cable entry knockouts at the rear)
Number of locations	4
RAL-number	7035

Degree of protection	NEMA 3R IP67/IP69K
Opening diameter	22.5 mm

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Connection to SmartWire-DT	No
----------------------------	----

Force for positive opening - min	0 N
----------------------------------	-----

10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecI@ss10.0.1-27-37-12-05 [AKF023014])		
Number of command positions		4
Construction type housing		Surface mounting housing
Material housing		Plastic
Housing material quality		Other
Diameter openings	mm	22.5
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		3R
Width	mm	186
Height	mm	56
Depth	mm	80