



Label, emergency switching off, yellow, D=60mm, 4 languages, DE, EN, FR, IT

Part no. M22-XBK1

216483

**EL Number
(Norway)**

4315293

Product name	Eaton Moeller® series M22 Accessory Emergency-Stop label
Part no.	M22-XBK1
EAN	4015082164836
Product Length/Depth	60 millimetre
Product height	1 millimetre
Product width	60 millimetre
Product weight	0.003 kilogram
Compliances	Contact Manufacturer
Certifications	UL/CSA certification not required LR DNV GL
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Emergency-Stop label
Public Consumption	Yes
Product Family Description	ES-PMCC-ICP-Eaton RMQ-Titan M22 Modular pilot devices
Globally Marketable	Yes

Color	Yellow
Inscription	Other
Language	Several
RAL-number	1004
Shape	Round

Degree of protection	IP66
Size	60 x 60 mm

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Connection to SmartWire-DT	No
----------------------------	----

Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss10.0.1-27-37-12-25 [AKF043014])			
Meaning of the imprint			Other
Language of the imprint			Several
Imprint ISO symbols			None
Colour			Yellow
Shape			Round
Width		mm	60
Height		mm	1
Outer diameter		mm	60