



Blanking plug, black

Part no. M22S-B
216390
EL Number 4355409
(Norway)

Product name	Eaton Moeller® series M22 Accessory Blanking plug
Part no.	M22S-B
EAN	4015082163907
Product Length/Depth	30 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.006 kilogram
Compliances	Contact Manufacturer
Certifications	CE
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Blanking plug
Public Consumption	Yes
Product Family Description	ES-PMCC-ICP-Eaton RMQ-Titan M22 Modular pilot devices
Globally Marketable	Yes

Color	Black
Functions	For closing off of spare mounting locations
Material	Plastic
RAL-number	9005

Degree of protection	NEMA 3R IP67 NEMA 4X NEMA 13 IP69K IP66 NEMA 12
Degree of protection (front side)	NEMA Other IP67/IP69K
Opening diameter	22 mm

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Connection to SmartWire-DT	No
----------------------------	----

Force for positive opening - min	0 N
----------------------------------	-----

Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity P _{diss}	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (I _n)	0 A
Static heat dissipation, non-current-dependent P _{vs}	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Blind cover for command devices (EC002023)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Blind cover for control circuit devices (ecl@ss10.0.1-27-37-12-39 [ACN976011])			
Material			Plastic
Construction type lens			Round
Hole diameter		mm	22
Width opening		mm	0
Height opening		mm	0
Colour			Black