



**Ring**

Part Number	Stud Size	Pack Qty
QRR3	3mm	100
QRR37	3.7mm	100
QRR4	4mm	100
QRR5	5mm	100
QRR6	6mm	100
QRR8	8mm	100
QRR10	10mm	100
QRR12	12mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 19A Voltage (max): 600V



**Male Push-on**

Part Number	Tab Size mm	Pack Qty
QRPO28M5	2.8mm X 0.5mm	100
QRPO28M8	2.8mm X 0.8mm	100
QRPO48M5	4.8mm X 0.5mm	100
QRPO48M8	4.8mm X 0.8mm	100
QRPO63M	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 10A Voltage (max): 600V



**Female Push-on**

Part Number	Tab Size mm	Pack Qty
QRPO28F5	2.8mm X 0.5mm	100
QRPO28F8	2.8mm X 0.8mm	100
QRPO48F5	4.8mm X 0.5mm	100
QRPO48F8	4.8mm X 0.8mm	100
QRPO63F	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 10A Voltage (max): 600V



**Spade**

Part Number	Stud Size	Pack Qty
QRF3	3mm	100
QRF3N	3.5mm	100
QRF4N	4mm	100
QRF5	5mm	100
QRF6	6mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 19A Voltage (max): 600V



**Female Push-on Fully Insulated**

Part Number	Tab Size mm	Pack Qty
QRFPO28F5	2.8mm X 0.5mm	100
QRFPO28F8	2.8mm X 0.8mm	100
QRFPO48F5	4.8mm X 0.5mm	100
QRFPO48F8	4.8mm X 0.8mm	100
QRFPO63F	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 10A Voltage (max): 600V



**Blade**

Part Number	Dia x Length mm	Pack Qty
QRBL10	2.3mm X 10mm	100
QRBL14	2.3mm X 14mm	100
QRBL18	2.3mm X 18mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 19A Voltage (max): 600V



**Butt**

Part Number	Pack Qty
QRB	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 19A Voltage (max): 600V



**Piggy Back Push-on Connector**

Part Number	Tab Size mm	Pack Qty
QRPOA63	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 10A Voltage (max): 600V



**Pin**

Part Number	Dia x Length mm	Pack Qty
QRP12	1.9mm X 12mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 19A Voltage (max): 600V



**Heat Shrink Butt**

Part Number	Pack Qty
QHSB1	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 19A Voltage (max): 600V



**Male Bullet**

Part Number	Bullet Dia mm	Pack Qty
QRAB4M	4mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 10A Voltage (max): 600V



**Female Bullet**

Part Number	Bullet Dia mm	Pack Qty
QRAB4F	4mm	100

Cable size range: 0.5 - 1.5mm<sup>2</sup>  
Current rating (max): 10A Voltage (max): 600V



**Ring**

Part Number	Stud Size	Pack Qty
QBR3	3mm	100
QBR37	3.7mm	100
QBR4	4mm	100
QBR5	5mm	100
QBR6	6mm	100
QBR8	8mm	100
QBR10	10mm	100
QBR12	12mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 24A Voltage (max): 600V



**Male Push-on**

Part Number	Tab Size mm	Pack Qty
QBPO48M5	4.8mm X 0.5mm	100
QBPO48M8	4.8mm X 0.8mm	100
QBPO63M	6.3mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V



**Female Push-on**

Part Number	Tab Size mm	Pack Qty
QBPO48F5	4.8mm X 0.5mm	100
QBPO48F8	4.8mm X 0.8mm	100
QBPO63F	6.3mm X 0.8mm	100
QBPO85F	8.5mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V



**Spade**

Part Number	Stud Size	Pack Qty
QBF3	3mm	100
QBF3N	3.5mm	100
QBF4N	4mm	100
QBF5	5mm	100
QBF6	6mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 24A Voltage (max): 600V



**Female Push-on Fully Insulated**

Part Number	Tab Size mm	Pack Qty
QBFPO48F5	4.8mm X 0.5mm	100
QBFPO48F8	4.8mm X 0.8mm	100
QBFPO63F	6.3mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V



**Blade**

Part Number	Dia x Length mm	Pack Qty
QBBL9	2.8mm X 9mm	100
QBBL18	2.2mm X 18mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 24A Voltage (max): 600V



**Butt**

Part Number	Pack Qty
QBB	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V



**Piggy Back Push-on Connector**

Part Number	Tab Size mm	Pack Qty
QBPOA63	6.3mm X 0.8mm	100


Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V



**Pin**

Part Number	Dia x Length mm	Pack Qty
QBP12	1.9mm X 12mm	100


Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 27A Voltage (max): 600V



**Heat Shrink Butt**

Part Number	Pack Qty
QHSB2	100


Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 27A Voltage (max): 600V



**Male Bullet**

Part Number	Bullet Dia mm	Pack Qty
QBAB4M	4mm	100
QBAB5M	5mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V



**Female Bullet**

Part Number	Bullet Dia mm	Pack Qty
QBAB4F	4mm	100
QBAB5F	5mm	100

Cable size range: 1.5 - 2.5mm<sup>2</sup>  
Current rating (max): 15A Voltage (max): 600V