

DOWNLIGHTS

SUN CIRCULAR LED PANEL

6W

9W

12W

18W

24W



CONSTRUCTION:

- White Polycarbonate Housing
- Opal Polystyrene diffuser
- Spring steel mounting springs
- Pressed steel mounting bracket

FEATURES:

- Range of 5 Wattages & diameters
- Emergency, DALI or Analogue dimmable available
- Provides functional dimming or Daylight Harvesting energy saving
- White chamfered trim
- Clean looking with virtually no projection below the ceiling
- The light appears to be emitted direct from the ceiling surface
- Slim profile body
- Fits within the thickness of the ceiling
- Ideal for shallow voids or where there are numerous other services



WARRANTY



RATED HOURS



LUMENS PER W



IK RATING



IP RATING



OPERATING VOLTAGE



BEAM ANGLE



CCT




SAFETY CLASS

DIMENSIONS (mm)

	Diameter	Cut-out	Depth
R120LEDC30N-01	120	110	25
R120LEDC40N-01	120	110	25
R150LEDC30N-01	145	135	25
R150LEDC40N-01	145	135	25
R170LEDC40N-01	170	160	25
R225LEDC30N-01	225	210	25
R225LEDC40N-01	225	210	25
R300LEDC40N-01	300	285	25

ACCESSORIES

R3EMPK4-PSU	3 Hour Emergency Pack with LiFePO4 battery, c/w Swift Connector
HED6045/D2	Dali switch dim, 45W LED current selectable driver w/ 30cm cable +DC connector
R24DIM-PSU	24W dimmable driver for R300LED
RLA400DT	LOADPRO 150W LED Dimmer



Scan here for more product information

DOWNLIGHTS

SUN CIRCULAR LED PANEL

3000K	R120LEDC30N-01	R150LEDC30N-01	R225LEDC30N-01		
3000K Emergency	R170LEDC30-01E				
4000K	R120LEDC40N-01	R150LEDC40N-01	R170LEDC40N-01	R225LEDC40N-01	R300LEDC40N-01
4000K Analogue Dim	R150LEDC40N-01AD				
4000K Emergency	R150LEDC40N-01E		R170LEDC40-01E	R225LEDC40N-01E	R300LEDC40-01E
Comparable to (PL):	13W PL	18W PL	24W PL	2x18W PL	2x26W PL
Total Power (W):	6.2/6.0	9.5/9.3	11.2	19.9/19.6	23.6
Total Light Output (lm):	510/500	910/930	1,120	1,940/2,120	2,760
Efficacy (lm/cctW):	82/83	97/101	100	98/108	117
Lux at 1m (lux):	180/180	320/330	390	710/780	1,010
CCT (K):	3000/4000	3000/4000	4000	3000/4000	4000
CRI:	80	80	80	80	80
Power Factor (PF):	0.5	0.5	0.9	0.95	0.95
Weight (kg):	0.2	0.28	0.32	0.55	0.7
Carton Qty:	50	40	30	20	10
SEAI approved	E A G		F A G	E A G	E A G
Triple E registered	E A G		E A G	E A G	E A G

CONVERSIONS AVAILABLE



