

PUSH-FIT CONNECTORS

For Solid, Stranded or Fine Stranded Cables



SDK Type - T90

- General purpose
- Stacking design
- Colour coded for easy identification
- 24A
- Max 2.5mm² - Solid / Stranded



Cool Splice Type

- General purpose
- Stacking design
- Colour coded for easy identification
- <20A
- Max 4.0mm² - Solid / Stranded



Lever Type - T85

- 32A
- Max 4mm² - Solid / Stranded / Fine



Miniature Type - T60

- Super-compact
- 24A
- Colour coded for easy identification
- Max 2.5mm² - Solid



Big Red Type - T105

- General purpose/heavy duty
- 41A
- Max 6mm² - Solid / Stranded



Lighting Type - T90

- Space saving design
- 24A
- Max 2.5mm² - Solid / Stranded / Fine

▶ SDK Type - T90



Standard of Compliance - **BS 60998-1 60998-2-2**

Specification -

- 24A / 450V • 0.5 - 2.5mm² solid cable • 1.5 - 2.5mm² stranded cable
- **Not suitable for fine stranded cable** • Interlocking stacking design

Certified -

| List No. | Conductors | Conductor Entry | Pack Qty |
|----------|------------|-----------------------|----------|
| SDK3 | 3 | 3 x solid or stranded | 100 |
| SDK5 | 5 | 5 x solid or stranded | 50 |
| SDK8 | 8 | 8 x solid or stranded | 30 |

▶ Cool Splice Type



Standard of Compliance - **IEC 60998-2-3, UL 486C,**

Specification -

- <20A • 0.75 - 1.5mm² solid, stranded (Red)
- 1.5 - 2.5mm² solid, stranded (Blue)
- 2.5 - 4.0mm² solid, stranded (Yellow)
- IPX8 • Interlocking stacking design

Certified -

| List No. | Conductors | Conductor Entry | Pack Qty |
|----------|------------|---------------------|----------|
| NCL1 | 2 | 2 x solid, stranded | 1 |
| NCL2 | 2 | 2 x solid, stranded | 1 |
| NCL3 | 2 | 2 x solid, stranded | 1 |
| NCL4 | 2 | 2 x solid, stranded | 1 |
| NCL5 | 2 | 2 x solid, stranded | 1 |

▶ Lever Type - T85



Standard of Compliance - **BS 60998-1 60998-2-2**

Specification -

- 32A / 450V • 0.2 - 4mm² solid cable • 0.2 - 4mm² stranded cable
- 0.34 - 4mm² fine stranded cable

Certified -

| List No. | Conductors | Conductor Entry | Pack Qty |
|----------|------------|-----------------------------|----------|
| VPC2 | 2 | 2 x solid, stranded or fine | 100 |
| VPC3 | 3 | 3 x solid, stranded or fine | 50 |
| VPC5 | 5 | 5 x solid, stranded or fine | 25 |

▶ Miniature Type - T60



Standard of Compliance - **BS 60998-1 60998-2-2**

Specification -

- 24A / 450V
- 0.5 - 2.5mm² solid cable

Certified -

| List No. | Conductors | Conductor Entry | Pack Qty |
|----------|------------|-----------------|----------|
| MCP2 | 2 | 2 x solid | 100 |
| MCP3 | 3 | 3 x solid | 50 |
| MCP4 | 4 | 4 x solid | 50 |
| MCP5 | 5 | 5 x solid | 50 |
| MCP8 | 8 | 8 x solid | 50 |

▶ Big Red Type - T105



Standard of Compliance - **BS 60998-1 60998-2-2**

Specification -

- 41A / 400V
- 2.5 - 6mm² stranded cable
- 2.5 - 6mm² solid cable
- **Not suitable for fine stranded cable**

Certified -

| List No. | Conductors | Conductor Entry | Pack Qty |
|----------|------------|---------------------|----------|
| BRC3 | 3 | 2 x solid, stranded | 25 |

▶ Lighting Type - T90



Standard of Compliance - **BS 60998-1 60998-2-2**

Specification - • 24A / 450V

- Lighting side: 0.5 - 2.5mm² stranded cable
- 0.5 - 2.5mm² solid cable
- 0.5 - 2.5mm² fine stranded cable
- Installation side: 0.75 - 2.5mm² solid cable

Certified -

| List No. | Conductors | Conductor Entry Lighting Side | Conductor Entry Install Side | Pack Qty |
|----------|------------|-------------------------------|------------------------------|----------|
| LPC1 | 2 | 1 x solid, stranded or fine | 1 x solid | 50 |
| LPC2 | 3 | 1 x solid, stranded or fine | 2 x solid | 50 |