



KLMB4W

### Marshalling Boxes - Wire In, Plug Out

#### Characteristics:

- The KLMB marshalling box allows the connection and control of multiple luminaires. The marshalling box utilises a robust extruded aluminium body.
- 7 Pole.
- 4, 6, 8, 10 & 12 outlets.
- 16A Rated BS 5733:2010 .
- Short circuit tested: 1500A conditional rating.

Description	Cat ref.
<b>Marshalling Box, Single Supply, Wire In, Plug Out</b>	
4 Way	<b>KLMB4W</b>
6 Way	<b>KLMB6W</b>
8 Way	<b>KLMB8W</b>
10 Way	<b>KLMB10W</b>
12 Way	<b>KLMB12W</b>
<b>Marshalling Box, Dual Channel, Wire In, Plug Out</b>	
8 Way, 4/4	<b>KLMB244W</b>
10 Way, 5/5	<b>KLMB255W</b>
12 Way, 6/6	<b>KLMB266W</b>



KLMB5P

### Marshalling Boxes - Plug In, Plug Out

#### Characteristics:

- The KLMB marshalling box allows the connection and control of multiple luminaires. The marshalling box utilises a robust extruded aluminium body.
- 7 Pole.
- 5, 7, 9 & 11 outlets.
- 16A Rated BS 5733:2010 .
- Short circuit tested: 1500A conditional rating.

Description	Cat ref.
<b>Marshalling Box, Single Supply, Plug In, Plug out</b>	
5 Way	<b>KLMB5P</b>
7 Way	<b>KLMB7P</b>
9 Way	<b>KLMB9P</b>
11 Way	<b>KLMB11P</b>



K7B1M075WPCR

### Klik 7 Pre-wired Plugs with Sockets

#### Characteristics:

- Connections to the luminaire are made via a pre-wired plug and lead. All leads are low smoke zero halogen and are factory connected and tested.
- Standard, digital and emergency luminaires.
- Short circuit tested: 1500A conditional rating.
- Cable standard BS 7211.

Description	Cat ref.
<b>Pre-wired Plugs and Sockets for Standard Luminaires</b>	
6A Luminaire Lead 1.5m 0.75mm <sup>2</sup> 3 Core Plug to Wire + KLPCR7	<b>K7B1M075WPCR ★</b>
6A Luminaire Lead 3m 0.75mm <sup>2</sup> 3 Core Plug to Wire + KLPCR7	<b>K7B3M075WPCR ★</b>
<b>Pre-wired Plugs and Sockets for Standard Luminaires with Emergency</b>	
6A Luminaire Lead 1.5m 0.75mm <sup>2</sup> 4 Core Plug to Wire + KLPCR7	<b>K7J1M075WPCR ★</b>
6A Luminaire Lead 3m 0.75mm <sup>2</sup> 4 Core Plug to Wire + KLPCR7	<b>K7J3M075WPCR ★</b>
<b>Pre-wired Plugs and Sockets for Dimmable Luminaires</b>	
6A Luminaire Lead 1.5m 0.75mm <sup>2</sup> 5 Core Plug to Wire + KLPCR7	<b>K7P1M075WPCR ★</b>
6A Luminaire Lead 3m 0.75mm <sup>2</sup> 5 Core Plug to Wire + KLPCR7	<b>K7P3M075WPCR ★</b>
<b>Pre-wired Plugs and Sockets for Dimmable Luminaires with Emergency</b>	
6A Luminaire Lead 1.5m 0.75mm <sup>2</sup> 6 Core Plug to Wire + KLPCR7	<b>K7T1M075WPCR ★</b>
6A Luminaire Lead 3m 0.75mm <sup>2</sup> 6 Core Plug to Wire + KLPCR7	<b>K7T3M075WPCR ★</b>