

3 Pin Plug Socket Outlets

Characteristics:

- 6A socket outlets are used in conjunction with 6A plugs to provide a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733:2010.
- Suitable for use with standard Klik 3 pin plug.
- **S27** socket is supplied in plug-in ceiling rose, Cat. Ref. **PCR2000**.
- **S27** socket will accept **A1** cover.
- **S26/TC** socket is an **S26** architrave socket pre-assembled with a trunking clamp.

Description	Quantity	Cat ref.
Ultra Flush Socket White	10	S21
Architrave Socket White	10	S26
Architrave Socket comes with Trunking Clamp	10	S26/TC
3 Pin Round Socket White	10	S27
Ultra Flush Round Socket White	10	S28



S27

4 Pin (Including Auxiliary) Plug Socket Outlets

Characteristics:

- Klik auxiliary 6A socket outlets are used in conjunction with Klik auxiliary 6A plugs to provide a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733:2010.
- Suitable for use with standard Klik 4 pin plug.
- **S64AX** socket is supplied in plug-in ceiling rose, Cat. Ref. **PCR2000**.
- **S64AX** socket will accept **A1** cover.
- **S65AX** socket is a square variant.
- All sockets have 5 terminations: line, neutral, CPC, auxiliary and loop-in.
- Can be used with Klik 3 or 4 pin plug.

Description	Quantity	Cat ref.
4 Pin Round Socket White	10	S64AX
4 Pin Square Socket White	10	S65AX



S64AX



S65AX

Moulded Mounting Boxes

Description	Quantity	Cat ref.
Round Surface Box White	10	MB2



MB2